WATER WELL REC	CORD	Form W	WC-5	Di	vision of Wate	r Resources App. N	o. L	
1 LOCATION OF WA	TER WELL:	Fraction		Section	on Number	Township No.		
Street/Rural Address of	of Well Location: i					System (GPS) in		
from nearest town or in				Latitu	ıde:		(in decimal degrees)	
							(in decimal degrees)	
2441 break wood DR. OHAWE, KS.					Elevation:			
2 WATER WELL OW	Decke	(A) -		Datum: WGS 84, NAD 83, NAD 27 Collection Method:				
RR#, Street Address,		DR.	Collec	<u>ction Metnod:</u> GPS unit <i>(</i> Mal	ke/Model·)		
City, State, ZIP Code	0.60,000			☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey				
	Ottan	Ja, Ks. 6	6224	Est. A	ccuracy: \square	<3 m, 3-5 m, 3	5-15 m, $\square > 15$ m	
3 LOCATE WELL			2 ^ /		_	4 - doo'	Bores Place	
WITH AN "X" IN	4 DEPTH OF C	COMPLETED WELL		?	ft.	, ,,,,	111/7/2	
SECTION BOX:								
	WELL'S STATE	tost dota: Well water	VD .\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	i. below i	iand surface i	hours num	ay/yr	
Pump test data: Well water was								
NW NE	Bore Hole Diam	eter 8314 in to	25	ft and .	in.	to SAS.	ft.	
W X E	WELL WATER	TO BE USED AS:	Public wa	iter suppl	ly 💹 Ge	othermal \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	njection well	
CW CE	☐ Domestic	☐ Feedlot ☐	Oil field wa	ter suppl	y 🗋 De	ewatering) 🗍 🤇	Other (Specify below)	
SW SE								
Was a chemical/bacteriological sample submitted to Department? Yes X No								
S If yes, mo/day/yr sample was submitted								
1 mile Water well disinfected? ☐ Yes 🔀 No								
5 TYPE OF CASING USED: Steel PVC Other . M. D Rolly Sthyles								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter								
Casing height about land surface								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel ☐ PVC N → ☐ Other (Specify)								
SCREEN OR PERFORATION OPENINGS ARE: N/A								
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
From								
From								
6 GROUT MATERIAL: ☐ Neat cement ☐ Gement grout ☐ Bentonite ☐ Other								
Grout Intervals: From 3.20 ft. to 3 ft., From								
What is the nearest source of possible contamination:								
Septic tank	Lateral lin	es Pit privy	Livestock		Insecticide		er (specify below)	
Sewer lines	Cesspool		Fuel stora		Abandoned			
Watertight sewer l	Seepage p	it Feedyard	Fertilizer		Oil well/ga			
Direction from well	LITHOLOG		FROM	TO TO			GGING INTERVAL	
	136147	10 100	I KOW	10	LITIO. L	oo (conc.) or 1 LC	GOING INTERVAL	
	, ,	e trape or						
3 - 9	estone)						end and the service of the service o	
86 85 C	ale							
86 85 51 85 98 Lu 98 110 51	me store!		200	3	4-22	o' Bares	Phoned	
98 10 5	Tolo,)	1 3000		''''	
	nestane							
	1,000							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, a reconstructed, or plugged								
under my jurisdiction and was completed on (mo/day/year)								
Kansas Water Well Contractor's License No. 5.6 This Water Well Record was completed on (mo/day/year)								
under the business name of L. v.q. a.s								
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								
http://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212								