

# WATER WELL RECORD Form WWC-5

☐ Original Record ☐ Correction ☐ Change in Well Use

Division of Water  
Resources App. No.

Well ID

<b>1 LOCATION OF WATER WELL:</b> County: <u>Marion</u>	Fraction <u>N 1/4 Sec 1/4</u>	Section Number <u>36</u>	Township Number <u>T 17 S</u>	Range Number <u>R 24 E</u>
---	-------------------------------	--------------------------	-------------------------------	----------------------------

<b>2 WELL OWNER:</b> Last Name: <u>Novak</u> First: <u>Kelly</u> Business: <u>3036 Limestone</u> Address: <u>Tampa</u> State: <u>KS</u> ZIP: <u>67483</u> City: <u>Tampa</u>	Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here: <input type="checkbox"/> <u>1 1/2 S Tampa, KS</u>
---	---

<b>3 LOCATE WELL WITH "X" IN SECTION BOX:</b> N W E S 1 mile	<b>4 DEPTH OF COMPLETED WELL:</b> <u>75</u> ft. Depth(s) Groundwater Encountered: 1) <u>65</u> ft. 2) <u>75</u> ft. 3) <u>75</u> ft., or 4) <input type="checkbox"/> Dry Well WELL'S STATIC WATER LEVEL: <u>41</u> ft. <input type="checkbox"/> below land surface, measured on (mo-day-yr) <input checked="" type="checkbox"/> above land surface, measured on (mo-day-yr) <u>11-20-12</u> Pump test data: Well water was <u>75</u> ft. after <u>20</u> hours pumping <u>75</u> gpm Well water was <u>75</u> ft. after <u>20</u> hours pumping <u>75</u> gpm Estimated Yield: <u>20</u> gpm Bore Hole Diameter: <u>5 1/8</u> in. to <u>7 1/2</u> ft. and <u>7 1/2</u> in. to <u>7 1/2</u> ft.	<b>5 Latitude:</b> ..... (decimal degrees) <b>Longitude:</b> ..... (decimal degrees) Datum: <input type="checkbox"/> WGS 84 <input type="checkbox"/> NAD 83 <input type="checkbox"/> NAD 27 Source for Latitude/Longitude: <input type="checkbox"/> GPS (unit make/model: .....) (WAAS enabled? <input type="checkbox"/> Yes <input type="checkbox"/> No) <input type="checkbox"/> Land Survey <input type="checkbox"/> Topographic Map <input type="checkbox"/> Online Mapper: .....
---	---	--

<b>7 WELL WATER TO BE USED AS:</b> 1. Domestic: <input type="checkbox"/> Household <input type="checkbox"/> Lawn & Garden <input checked="" type="checkbox"/> Livestock 2. <input type="checkbox"/> Irrigation 3. <input type="checkbox"/> Feedlot 4. <input type="checkbox"/> Industrial 5. <input type="checkbox"/> Public Water Supply: well ID ..... 6. <input type="checkbox"/> Dewatering: how many wells? ..... 7. <input type="checkbox"/> Aquifer Recharge: well ID ..... 8. <input type="checkbox"/> Monitoring: well ID ..... 9. Environmental Remediation: well ID ..... <input type="checkbox"/> Air Sparge <input type="checkbox"/> Soil Vapor Extraction <input type="checkbox"/> Recovery <input type="checkbox"/> Injection 10. <input type="checkbox"/> Oil Field Water Supply: lease ..... 11. Test Hole: well ID ..... <input type="checkbox"/> Cased <input type="checkbox"/> Uncased <input type="checkbox"/> Geotechnical 12. Geothermal: how many bores? ..... a) Closed Loop <input type="checkbox"/> Horizontal <input type="checkbox"/> Vertical b) Open Loop <input type="checkbox"/> Surface Discharge <input type="checkbox"/> Inj. of Water 13. <input type="checkbox"/> Other (specify): .....
---

Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ☒ No If yes, date sample was submitted: .....  
Water well disinfected? ☒ Yes ☐ No

**8 TYPE OF CASING USED:** ☐ Steel ☒ PVC ☐ Other ..... CASING JOINTS: ☒ Glued ☐ Clamped ☐ Welded ☐ Threaded  
Casing diameter 5 in. to 7 1/2 ft., Diameter 50 in. to 72 ft., Diameter 50 in. to 72 ft.  
Casing height above land surface 25 in. Weight SDR26 lbs./ft. Wall thickness or gauge No. 214

TYPE OF SCREEN OR PERFORATION MATERIAL:  
☐ Steel ☐ Stainless Steel ☐ Fiberglass ☒ PVC ☐ Other (Specify) .....  
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:  
☐ Continuous Slot ☐ Mill Slot ☐ Gauze Wrapped ☒ Torch Cut ☐ Drilled Holes ☐ Other (Specify) .....  
☐ Louvered Shutter ☐ Key Punched ☐ Wire Wrapped ☒ Saw Cut ☐ None (Open Hole)  
SCREEN-PERFORATED INTERVALS: From 50 ft. to 72 ft., From 50 ft. to 72 ft., From 50 ft. to 72 ft.  
GRAVEL PACK INTERVALS: From 20 ft. to 25 ft., From 20 ft. to 25 ft., From 20 ft. to 25 ft.

**9 GROUT MATERIAL:** ☐ Neat cement ☐ Cement grout ☒ Bentonite ☐ Other .....  
Grout Intervals: From 0 ft. to 20 ft., From 20 ft. to 25 ft., From 20 ft. to 25 ft.

Nearest source of possible contamination:  
☐ Septic Tank ☐ Lateral Lines ☐ Pit Privy ☐ Livestock Pens ☐ Insecticide Storage  
☐ Sewer Lines ☐ Cess Pool ☐ Sewage Lagoon ☐ Fuel Storage ☐ Abandoned Water Well  
☐ Watertight Sewer Lines ☐ Seepage Pit ☐ Feedyard ☐ Fertilizer Storage ☐ Oil Well/Gas Well  
☐ Other (Specify) .....  
Direction from well? None within 4 mi Distance from well? In pasture ft.

10 FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHO. LOG (cont.) or PLUGGING INTERVALS
0	3	Top Soil			
3	35	Yellow Clay mixed Shale			
35	64	Blue Shale			
64	65	Crumbled Shale + Water			
65	75	Gray Shale			

**11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:** This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged under my jurisdiction and was completed on (mo-day-yr) 11-20-12 and this record is true to the best of my knowledge and belief.  
Kansas Water Well Contractor's License No. 180 This Water Well Record was completed on (mo-day-yr) 11-30-12  
under the business name of Backus Drilling