			R WELL RECOR	RD Forr	n WWC-5		2a-1212				
LOCATION OF WA		Fraction				tion Numbe		wnship Nu			ge Number
County: Frank	lin	SE 1/4		NE	1/4	1	Т	17	S	R 2	20 E/W
Distance and direction		•		located wit	thin city?						
1	miles Nor		eoria								
WATER WELL OV		ugh									
RR#, St. Address, Bo	x # :							-		Division of	Water Resource
City, State, ZIP Code								pplication			· · · · · · · · · · · · · · · · · · ·
I LOCATE WELL'S L AN "X" IN SECTIO	OCATION WITH 4										
AIT X III 020110	De		water Encounter								
ī !!	! W		WATER LEVEL								
\\w	NE	Pum	p test data: We	ll water wa	ıs	$\dots \dots \ \text{ ft. }$	after		hours pu	mping	gpm
J [''''	Es		gpm: We								
<u></u>	@ I _ Bo	re Hole Diame	eter . 57. / 8								
≦ " !	! W	ELL WATER T	TO BE USED AS	: 5 P	ublic wate	er supply	8 Air co	nditioning	11	Injection v	vell ecify below)
ī	SE	1 Domestic	3 Feedlot	6 O	il field wa	ter supply	9 Dewa	tering	12 Oh 202	Other (Sp	ecify below)
;;;		2 Irrigation	4 Industria	al 7 La	awn and g	garden only	(10) Monit	oring well	Obse	cvatic)II
	l Wa	as a chemical/l	bacteriological sa	mple subm	itted to De	epartment?	Yes	NoX	; If yes	, mo/day/y	r sample was sub
	s mit	tted				W	Vater Well	Disinfected	? Yes	1	No X
TYPE OF BLANK	CASING USED:		5 Wrought iron	l	8 Concre	ete tile	CA	SING JOIN	ITS: Glue	d (Clamped
1 Steel	3 RMP (SR)		6 Asbestos-Ce			(specify bel					
2 PVC	4 ABS		7 Fiberglass								ζ
Blank casing diameter											
Casing height above I	and surface30.		.in., weight		, , , , ,	lbs	s./ft. Wall t	hickness o	gauge N	o. "Scl	
TYPE OF SCREEN C	R PERFORATION N	MATERIAL:			- (PV	رے		10 Asbe	stos-ceme	ent	
1 Steel	3 Stainless st	eel	5 Fiberglass		8 RM	IP (SR)		11 Othe	r (specify)		
2 Brass	4 Galvanized	steel	6 Concrete tile		9 AB	S		12 None	used (op	en hole)	
SCREEN OR PERFO	RATION OPENING8	ARE	5	Gauzed w	rapped		8 Saw	cut		11 None	(open hole)
1 Continuous sk	ot 🗷 Mill s	lot	6	Wire wrap	ped		9 Drille	ed holes			
2 Louvered shut	ter 4 Key p	punched	7	Torch cut			10 Othe	er (specify)			
SCREEN-PERFORAT	ED INTERVALS:	From	13. . .2 ft	. to 1	47	ft., Fr	rom		ft. t	o	
		From	ft	. to		ft., Fr	rom		ft. t	0	, ft
GRAVEL PA	CK INTERVALS:	From	120 ft	. to 1	47	ft., Fr	rom		ft. t	o	
		From	ft.	to		ft., Fr	rom		ft. t	ю	ft
GROUT MATERIAL	.: 1 Neat cem	ent	2 Cement grout				4 Other .				
Grout Intervals: Fro	m 0 ft.	to 12.0	0 ft., From .	. 147	ft.	to15.0) ft.,	From		ft. to .	
What is the nearest se	ource of possible cor	ntamination:				10 Live	estock pen	s	14 A	bandoned	water well
1 Septic tank 4 Lateral lines			7 Pit privy			11 Fue	11 Fuel storage 15 Oil well/Gas well				
2 Sewer lines	5 Cess po			ge lagoon			tilizer stora			ther (spec	
3 Watertight sev	ver lines 6 Seepage	pit	9 Feedy	ard			ecticide sto	•	<i>.</i>		
Direction from well?	North		·			How m	nany feet?	3200			
FROM TO		LITHOLOGIC	LOG		FROM	ТО			JGGING I	NTERVAL	S
0 1.4	Clay, da:	rk brown	n fat				Plua	ged 0	- 11	. 0	
1.4 10.0	Ls., brown							5000			
10.0 14.7	Shale, gra	•	•						-		
14.7 15.0	Ls., brown						Plug	ged 14	4.7 -	15.0	:
		,					1 - 49	904 -	<u> </u>		
	Well No. 7	r∩r _ 10	9								
	************	. OD = 1;							-		
											·.
	L	0=======			3	L	L				
	OR LANDOWNER'S			•	_					<i>/</i> \	
completed on (mo/day	/year) 6 / 14 4 . / . 9	13	· · · · · · · · · · · · · · · · · · ·			and this red	cord is true	to the bes	~ 111	owledge a	nd belief. Kansas
Water Well Contractor	's License No		This Wa	ater Well F	Record wa			ay/yr) A.	المصرا	13.2	
under the business na	me of LATNE	- 1 を 1	SIEKN			by (sign	nature) T	للبلا	w, +	mul	
INSTRUCTIONS: Use to	pewriter or ball point pen.							t answers. Ser			nsas Department