WATER WELL RECORD	Form W	WC-5	Division of Water	Resources App. No	o. L
1 LOCATION OF WATER W	ELL: Fraction NE 45 F 456	= 1/4 NW1/4	Section Number	Township No.	
				System (GPS) in	
from nearest town or intersection: If at owner's address, check here					
			Longitude: (in decimal degrees)		
			Elevation:		
2 WATER WELL OWNER:	Collection Method:	, , _			
RR#, Street Address, Box #: 29810 Hedge Lane GPS unit (Make/Model:)					
2 WATER WELL OWNER: 6 18 And Hager RR#, Street Address, Box #: 29810 Hedge Lane City, State, ZIP Code: PADIA KS			_ Digital Map/Pho	oto, 🔲 Topographic	c Map, Land Survey
	PADJA, KS		Est. Accuracy: \square <		
3 LOCATE WELL	TH OF COMPLETED WELL	T 35/)	Δ	3-350	deep Bores
WITH AN "X" IN 4 DEF SECTION BOX: Depth(TH OF COMPLETED WEL	L	π.		
[-] - [-]					
WELL S STATIC WATER DEVELWWW.SIt. below land surface incastred on inloyday/y1					
rump test data: Well water wast. after nours pumping gpm					
-NW - -NE - GT EST. YIELD. Ogpm, Well water was					
W Bore Hole Diameter					
WELL WATER TO BE USED AS: □ Public water supply ☐ Geothermal ☐ Injection well					
SW SE Domestic					
Was a chemical/bacteriological sample submitted to Department?					
S If yes, mo/day/yr sample was submitted					
1 mile Water well disinfected?					
5 TYPE OF CASING USED: Steel PVC Other .#.D., foly.th.yle.xe					
LANING JUINTS' Utilled Lambed ix welded Linteaged '					
Casing diameter in to 350 ft., Diameter in to ft., Diameter in to ft. Casing height desire land surface in, Weight 500 ft., Wall thickness or gauge No. 100 ft.					
Casing height dere land surface. 36 in Weight 500 II lhs/ft. Wall thickness or gauge No 126					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
Steel Stainless Steel PVC Other (Specify)					
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)					
☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify)					
SCREEN-PERFORATED INTERVALS: From					
From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From					
From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From 354. ft. to ft., From ft. to ft., From ft. to ft.					
Grout Intervals: From					
What is the nearest source of possible contamination:					
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)					
Sewer lines					
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well					
			rom well5.0		
	THOLOGIC LOG	FROM		OG (cont.) or PLU	GGING INTERVALS
6 7 Soul + Llag			64 Stale		
7 11 Linestone		 422 	78 Limester	4	
11 35 Shale		178 1	84 Ilale		
35 4 Limestone	2)	184 2	Lineston	e .	
Ly 79 - Soule			50 Stale	+ SANTTONG	2/
79 81 Limests	re 1		~~~~~~		
SI 98 State			3-350) Bores 1	lysed with
81 98 Slade 98 114 Limente	1-0.1	350	3 H156	Tr.1.1- 2	entantr.
114 130 Sante.			 	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
130 155 Lineste					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed, reconstructed, or plugged					
under my jurisdiction and was completed on (mg/day/year) 54					
Kansas Water Well Contractor's License No. 5.2.1					
under the business name of					
(white, blue, pink) to Kansas Department	t of Health and Environment, Bureau	of Water, Geolog	gy Section, 1000 SW Jac	kson St., Suite 420, 7	Topeka, Kansas 66612-1367.
Telephone 785-296-5522. Send one cop	by to WATER WELL OWNER and				
http://www.kdheks.gov/waterwell/index.html.					
KSA 82a-1212					