

1 LOCATION OF WATER WELL: County: <u>Marion</u>	Fraction <u>SW 1/4 SW 1/4 NW 1/4</u>	Section Number <u>14</u>	Township Number T <u>17</u> S	Range Number R <u>3</u> <u>EA</u>
--	---	-----------------------------	----------------------------------	--------------------------------------

Distance and direction from nearest town or city street address of well if located within city?

1W 1 1/2 S Ramona

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code	<u>Bernard Meysing</u> <u>RR1</u> <u>Ramona, KS. 67475</u>	Board of Agriculture, Division of Water Resources Application Number:
---	--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>113</u> ft. ELEVATION:
--	--

Depth(s) Groundwater Encountered 1 105 ft. 2. 105 ft. 3. 105 ft.

WELL'S STATIC WATER LEVEL 72 ft. below land surface measured on mo/day/yr 6-3-91

Pump test data: Well water was 25 gpm. Well water was 113 ft. after 6-3-91 hours pumping 25 gpm

Est. Yield 25 gpm. Well water was 113 ft. after 6-3-91 hours pumping 25 gpm

Bore Hole Diameter 2 1/2 in. to 113 ft. and 113 in. to 113 ft.

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	6 Oil field water supply	8 Air conditioning	11 Injection well
2 Irrigation	4 Industrial	7 Lawn and garden only	9 Dewatering	12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>Y</u> Clamped <u>Y</u>
------------------------------	----------------	-----------------	--

1 Steel

2 PVC

Blank casing diameter 5 in. to 93 ft. Dia 12 in. weight 12 lbs./ft. Wall thickness or gauge No. 12/14

Casing height above land surface 12 in.

3 RMP (SR)

4 ABS

6 Asbestos-Cement

7 Fiberglass

9 Other (specify below)

Welded

Threaded

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
SCREEN OR PERFORATION OPENINGS ARE:			8 Saw cut	11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 93 ft. to 113 ft. From 93 ft. to 113 ft. From 93 ft. to 113 ft.

GRAVEL PACK INTERVALS: From 93 ft. to 113 ft. From 93 ft. to 113 ft. From 93 ft. to 113 ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
-------------------	---------------	----------------	-------------	---------

Grout Intervals: From 4 ft. to 24 ft. From 4 ft. to 24 ft. From 4 ft. to 24 ft. From 4 ft. to 24 ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? <u>S</u>			How many feet? <u>70</u>	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>28</u>	<u>Yellow Clay & mixed Shale</u>			
<u>28</u>	<u>105</u>	<u>Blue Shale</u>			
<u>105</u>	<u>106</u>	<u>Water</u>			
<u>106</u>	<u>113</u>	<u>Blue Shale</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>6-3-91</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>180</u> This Water Well Record was completed on (mo/day/yr) <u>6-26-91</u> under the business name of <u>Backhus Drilling</u> by (signature) <u>Paul H. Backhus</u>
--