WATER WELL OWNER: Agri-Producers, Inc.  RR#, St. Address, Box # : 205 Main St.  Ity, State, ZIP Code : Tampa, KS 67483  LOCATE WELL'S LOCATON WITH AN' X' IN SECTION BOX:  Depth(s) Groundwater Encountered 1  WELL'S STATIC WATER LEVEL 33.46 ft. below TOG  Pump test data: Well water was  Bore Hole Diameter 8.25 in. to 80  WELL WATER TO BE USED AS: 5 Public water supply  1 Domestic 3 Feed lot 6 Oil field water supply  2 Irrigation 4 Industrial 7 Lawn and garden (dome:  Was a chemical/bacteriological sample submitted to Department submitted  TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify be 2 PVC 4 ABS 7 Fiberglass  Blank casing diameter 2 in. to 70 ft., Dia in. to  Casing height above land surface 0 in., weight 0.703 Ibs./  TYPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)  2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS  SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped  1 Continuous slot 3 Mill slot 6 Wire wrapped  2 Louvered shutter 4 Key punched 7 Torch cut  SCREEN-PERFORATED INTERVALS: From 68 ft. to 80 ft.  From ft. to ft.	Board of Agriculture, Division of Water Resources Application Number:  EVATION:  ft. 2 ft. 3 ft.  C measured on mo/day/yr  ft. after hours pumping gpm  ft. after hours pumping gpm  ft. and in. to ft.  8 Air conditioning 11 Injection well 9 Dewatering 12 Other (Specify below)  stic) 10 Monitoring well 17 Yes No X If yes, mo/day/yr sample was Vater Well Disinfected? Yes No X  CASING JOINTS: Glued Clamped  Elow) Welded  Threaded Flush  ft., Dia in. to ft.  10 Asbestos-cement  11 Other (specify)
Agri-Producers, Inc.  Ref. St. Address, Box # : 205 Main St.  Ref. St. Address, Box # : 205 Main St.  LOCATE WELL OWNER: Agri-Producers, Inc.  Ref. St. Address, Box # : 205 Main St.  LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX:  WELL'S STATIC WATER LEVEL 33.46 ft. below TOCATON WITH AN "X" IN SECTION BOX:  Bore Hole Diameter 8.25 in. to 80 meters supply 1 Department Submitted  Depth(s) Groundwater Encountered 1 WELL'S STATIC WATER LEVEL 33.46 ft. below TOCATON WITH AN "X" IN SECTION BOX:  WELL WATER TO BE USED AS: 5 Public water supply 1 Domestic 3 Feed lot 6 Oil field water supply 2 Irrigation 4 Industrial 7 Lawn and garden (domes submitted was a chemical/bacteriological sample submitted to Department submitted  Depth (s) Groundwater Encountered 1 WELL'S STATIC WATER LEVEL 33.46 ft. below TOCATON WATER TO BE USED AS: 5 Public water supply 1 Domestic 3 Feed lot 6 Oil field water supply 2 Irrigation 4 Industrial 7 Lawn and garden (domes submitted was a chemical/bacteriological sample submitted to Department submitted  Depth (s) Groundwater Encountered 1 WELL'S STATIC WATER LEVEL 33.46 ft. below TOCATON WATER TO BE USED AS: 5 Public water supply 1 Domestic 3 Feed lot 6 Oil field water supply 2 Irrigation 4 Industrial 7 Lawn and garden (domes was a chemical/bacteriological sample submitted to Department submitted by 2 PVC 4 A ABS 7 Fiberglass  Blank casing diameter 2 in. to 70 ft., Dia in. to 1 in. to 2 in. to 70 ft., Dia in. to 2 in. to 7 PVC 2 PVC 4 ABS 5 Fiberglass 8 RMP (SR 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 5 GREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 5 GCREEN PERFORATED INTERVALS: From 70 ft. to 80 ft. From 68 ft. to 680 ft. From 68 ft. t	Board of Agriculture, Division of Water Resources Application Number:  EVATION:  ft. 2
WATER WELL OWNER: Agri-Producers, Inc.  R#, St. Address, Box # : 205 Main St.  Ity, State, ZIP Code : Tampa, KS 67483  LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX:  Depth(s) Groundwater Encountered 1  WELL'S STATIC WATER LEVEL 33.46 ft. below TOG  Pump test data: Well water was  Bore Hole Diameter 3.25 in. to 80  WELL WATER TO BE USED AS: 5 Public water supply 1 Domestic 3 Feed lot 6 Oil field water supply 2 Irrigation 4 Industrial 7 Lawn and garden (dome: Was a chemical/bacteriological sample submitted to Department submitted  TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify be 2 PVC) 4 ABS 7 Fiberglass  lank casing diameter 2 in. to 70 ft., Dia in. to asing height above land surface 0 in., weight 0.703 Ibs./ YPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS  CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 3 Mill slot 6 Wire wrapped 2 Louvered shutter 4 Key punched 7 Torch cut  CREEN-PERFORATED INTERVALS: From 70 ft. to 80 ft.  From ft. to ft.  GRAVEL PACK INTERVALS: From 68 ft. to 80 ft.	Application Number:  EVATION:  ft. 2 ft. 3 ft.  C measured on mo/day/yr  ft. after hours pumping gpm  ft. after hours pumping gpm  ft. and in. to ft.  8 Air conditioning 11 Injection well 9 Dewatering 12 Other (Specify below)  10 Monitoring well 12 Other (Specify below)  13 Yes No X if yes, mo/day/yr sample was Vater Well Disinfected? Yes No X  CASING JOINTS: Glued Clamped  Elow) Welded  Threaded Flush  ft., Dia in. to ft.  10 Asbestos-cement 11 Other (specify) 12 None used (open hole) 8 Saw cut 11 None (open hole) 9 Drilled holes
ty, State, ZIP Code : Tampa, KS 67483  LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX:  Depth of Completed Well	Application Number:  EVATION:  ft. 2 ft. 3 ft.  C measured on mo/day/yr  ft. after hours pumping gpm  ft. after hours pumping gpm  ft. and in. to ft.  8 Air conditioning 11 Injection well 9 Dewatering 12 Other (Specify below)  10 Monitoring well 12 Other (Specify below)  13 Yes No X If yes, mo/day/yr sample was vater Well Disinfected? Yes No X  CASING JOINTS: Glued Clamped  Elow) Welded  Threaded Flush  ft., Dia in. to ft.  10 Asbestos-cement 11 Other (specify) 12 None used (open hole) 8 Saw cut 11 None (open hole) 9 Drilled holes
ty, State, ZIP Code : Tampa, KS 67483  LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX:  Depth (s) Groundwater Encountered 1  WELL'S STATIC WATER LEVEL 33.46 ft. below TOC Pump test data: Well water was Bore Hole Diameter 8.25 in. to 80  WELL WATER TO BE USED AS: 5 Public water supply 1 Domestic 3 Feed lot 6 Oil field water supply 2 Irrigation 4 Industrial 7 Lawn and garden (dome: Was a chemical/bacteriological sample submitted to Departmen submitted  TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile 2 PVC 4 ABS 7 Fiberglass ank casing diameter 2 in. to 70 ft., Dia in. to asing height above land surface 0 in., weight 0.703 lbs./ PVPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 3 Mill slot 6 Wire wrapped 7 Torch cut CREEN-PERFORATED INTERVALS: From 70 ft. to 80 ft. GRAVEL PACK INTERVALS: From 68 ft. to 80 ft.	Application Number:  EVATION:  ft. 2 ft. 3 ft.  C measured on mo/day/yr  ft. after hours pumping gpm  ft. after hours pumping gpm  ft. and in. to ft.  8 Air conditioning 11 Injection well 9 Dewatering 12 Other (Specify below)  10 Monitoring well 12 Other (Specify below)  13 Yes No X If yes, mo/day/yr sample was vater Well Disinfected? Yes No X  CASING JOINTS: Glued Clamped  Elow) Welded  Threaded Flush  ft., Dia in. to ft.  10 Asbestos-cement 11 Other (specify) 12 None used (open hole) 8 Saw cut 11 None (open hole) 9 Drilled holes
NS State, ZIP Code  Tampa, KS 67483  LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX:  WELL'S STATIC WATER LEVEL  Depth(s) Groundwater Encountered 1  WELL'S STATIC WATER LEVEL  Pump test data: Well water was  Bore Hole Diameter  8.25 in. to  80  WELL WATER TO BE USED AS: 5 Public water supply  1 Domestic 3 Feed lot 6 Oil field water supply  2 Irrigation 4 Industrial 7 Lawn and garden (domes with was a chemical/bacteriological sample submitted to Department submitted  TYPE OF BLANK CASING USED:  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify be a saing height above land surface 0 in., weight 0.703 in. to  asing height above land surface 0 in., weight 0.703 in. to  Asing height above land surface 1 State 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)  2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS  CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped  1 Continuous slot 3 Mill slot 6 Wire wrapped  2 Louvered shutter 4 Key punched 7 Torch cut  CREEN-PERFORATED INTERVALS: From 70 ft. to 80 ft.  From ft. to 80 ft.	ft. 2 ft. 3 ft.  C measured on mo/day/yr O9/13/13  ft. after hours pumping gpm ft. after hours pumping gpm ft. and in. to ft.  8 Air conditioning 11 Injection well 9 Dewatering 12 Other (Specify below)  10 Monitoring well 11 Yes No X If yes, mo/day/yr sample was Vater Well Disinfected? Yes No X  CASING JOINTS: Glued Clamped Blow) Welded  Threaded Flush ft., Dia in. to ft.  10 Asbestos-cement 11 Other (specify) 12 None used (open hole) 8 Saw cut 11 None (open hole) 9 Drilled holes
DEPTH OF COMPLETED WELL    NW   NE	ft. 2 ft. 3 ft.  C measured on mo/day/yr  ft. after hours pumping gpm ft. after hours pumping gpm ft. and in. to ft.  8 Air conditioning 11 Injection well 9 Dewatering 12 Other (Specify below)  10 Monitoring well 11 Yes No X If yes, mo/day/yr sample was Vater Well Disinfected? Yes No X  CASING JOINTS: Glued Clamped Flush  ft., Dia in. to ft.  10 Asbestos-cement 11 Other (specify) 12 None used (open hole) 8 Saw cut 11 None (open hole) 9 Drilled holes
Depth(s) Groundwater Encountered 1 WELL'S STATIC WATER LEVEL 33.46 ft. below TOO Pump test data: Well water was Est. Yield gpm: Well water was Bore Hole Diameter 8.25 in. to 80 WELL WATER TO BE USED AS: 5 Public water supply 1 Domestic 3 Feed lot 6 Oil field water supply 2 Irrigation 4 Industrial 7 Lawn and garden (dome: Was a chemical/bacteriological sample submitted to Departmen submitted  TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify be 2 PVC 4 ABS 7 Fiberglass ank casing diameter 2 in. to 70 ft., Dia in. to asing height above land surface 0 in., weight 0.703 lbs./ YPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 3 Mill slot 6 Wire wrapped 2 Louvered shutter 4 Key punched 7 Torch cut CREEN-PERFORATED INTERVALS: From 68 ft. to 80 ft.	ft. 2 ft. 3 ft. C measured on mo/day/yr 09/13/13  ft. after hours pumping gpm ft. after hours pumping gpm ft. and in. to ft.  8 Air conditioning 11 Injection well 9 Dewatering 12 Other (Specify below)  10 Monitoring well 17 Yes No X If yes, mo/day/yr sample was Vater Well Disinfected? Yes No X  CASING JOINTS: Glued Clamped Elow) Welded  Threaded Flush ft., Dia in. to ft.  10 Asbestos-cement 11 Other (specify) 12 None used (open hole) 8 Saw cut 11 None (open hole) 9 Drilled holes
WELL'S STATIC WATER LEVEL 33.46 ft. below TOO Pump test data: Well water was Est. Yield gpm: Well water was Bore Hole Diameter 8.25 in. to 80 WELL WATER TO BE USED AS: 5 Public water supply 1 Domestic 3 Feed lot 6 Oil field water supply 2 Irrigation 4 Industrial 7 Lawn and garden (dome: Was a chemical/bacteriological sample submitted to Department submitted  TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify because) 2 PVC 4 ABS 7 Fiberglass Iank casing diameter 2 in. to 70 ft., Dia in. to asing height above land surface 0 in., weight 0.703 lbs./ YPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 3 Mill slot 6 Wire wrapped 2 Louvered shutter 4 Key punched 7 Torch cut CREEN-PERFORATED INTERVALS: From 70 ft. to 80 ft. From ft. to 68 ft. to 80 ft.	the after hours pumping gpm ft. after hours pumping gpm ft. after hours pumping gpm ft. and in. to ft. 8 Air conditioning 11 Injection well 9 Dewatering 12 Other (Specify below) 12 Other (Specify below) 14 Present the present of th
Pump test data: Well water was  Est. Yield gpm: Well water was  Bore Hole Diameter 8.25 in. to 80  WELL WATER TO BE USED AS: 5 Public water supply 1 Domestic 3 Feed lot 6 Oil field water supply 2 Irrigation 4 Industrial 7 Lawn and garden (domes submitted Was a chemical/bacteriological sample submitted to Department submitted  TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify be 2 PVC 4 ABS 7 Fiberglass  lank casing diameter 2 in. to 70 ft., Dia in. to asing height above land surface 0 in., weight 0.703 lbs./  YPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS  CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 3 Mill slot 6 Wire wrapped 2 Louvered shutter 4 Key punched 7 Torch cut  CREEN-PERFORATED INTERVALS: From 68 ft. to 80 ft.  From ft. to ff.  GRAVEL PACK INTERVALS: From 68 ft. to 80 ff.	ft. after hours pumping gpm ft. after hours pumping gpm ft. and in. to ft.  8 Air conditioning 11 Injection well 9 Dewatering 12 Other (Specify below)  stic) 10 Monitoring well  t? Yes No X If yes, mo/day/yr sample was Vater Well Disinfected? Yes No X  CASING JOINTS: Glued Clamped  elow) Welded  Threaded Flush  ft., Dia in. to ft.  ft. Wall thickness or gauge No. SCH. 40  10 Asbestos-cement 11 Other (specify) 12 None used (open hole) 8 Saw cut 11 None (open hole) 9 Drilled holes
Bore Hole Diameter 8.25 in. to 80 WELL WATER TO BE USED AS: 5 Public water supply 1 Domestic 3 Feed lot 6 Oil field water supply 2 Irrigation 4 Industrial 7 Lawn and garden (domes submitted Was a chemical/bacteriological sample submitted to Department submitted  TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify be 2 PVC 4 ABS 7 Fiberglass  lank casing diameter 2 in. to 70 ft., Dia in. to assing height above land surface 0 in., weight 0.703 lbs./  YPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS  CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 3 Mill slot 6 Wire wrapped 2 Louvered shutter 4 Key punched 7 Torch cut  CREEN-PERFORATED INTERVALS: From 70 ft. to 80 ft.  From ft. to 68 ft. to 80 ft.	ft. after hours pumping gpm ft. and in. to ft.  8 Air conditioning 9 Dewatering 11 Injection well 12 Other (Specify below)  13 Injection well 14 Other (Specify below)  15 Yes No X If yes, mo/day/yr sample was No X  CASING JOINTS: Glued Clamped  Clamped Flush  16 Wall thickness or gauge No. SCH. 40  10 Asbestos-cement 11 Other (specify) 12 None used (open hole) 8 Saw cut 11 None (open hole) 9 Drilled holes
Bore Hole Diameter 8.25 in. to 80  WELL WATER TO BE USED AS: 5 Public water supply 1 Domestic 3 Feed lot 6 Oil field water supply 2 Irrigation 4 Industrial 7 Lawn and garden (domes submitted  Was a chemical/bacteriological sample submitted to Department submitted  TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify be 2 PVC 4 ABS 7 Fiberglass  lank casing diameter 2 in. to 70 ft., Dia in. to assing height above land surface 0 in., weight 0.703   Ibs./YPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS  CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 3 Mill slot 6 Wire wrapped 2 Louvered shutter 4 Key punched 7 Torch cut  CREEN-PERFORATED INTERVALS: From 70 ft. to 80 ft.  From ft. to 68 ft. to 80 ft.	ft. and in. to ft.  8 Air conditioning 9 Dewatering 11 Injection well 12 Other (Specify below)  10 Monitoring well 12 Other (Specify below)  11 Yes No X If yes, mo/day/yr sample was No X CASING JOINTS: Glued Clamped Clamped  12 Other (Specify below)  13 Welded Threaded Flush  14 Ft., Dia in. to ft.  15 Wall thickness or gauge No. SCH. 40  16 Asbestos-cement  17 Other (specify)  18 Saw cut 11 None (open hole)  19 Drilled holes
2 Irrigation 4 Industrial 7 Lawn and garden (domes was a chemical/bacteriological sample submitted to Department submitted  TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify be 2 PVC 4 ABS 7 Fiberglass  lank casing diameter 2 in. to 70 ft., Dia in. to asing height above land surface 0 in., weight 0.703 lbs./  YPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS in CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 3 Mill slot 6 Wire wrapped 2 Louvered shutter 4 Key punched 7 Torch cut in the continuous slot 5 From 70 ft. to 80 ft. From 6 ft. to	10   Monitoring well
2 Irrigation 4 Industrial 7 Lawn and garden (domes was a chemical/bacteriological sample submitted to Department submitted  TYPE OF BLANK CASING USED:  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify be a sink casing diameter 2 in. to 70 ft., Dia in. to asing height above land surface 0 in., weight 0.703 lbs./  YPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS  CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped  1 Continuous slot 3 Mill slot 6 Wire wrapped  2 Louvered shutter 4 Key punched 7 Torch cut  CREEN-PERFORATED INTERVALS: From 70 ft. to 80 ft.  From ft. to 68 ft. to 80 ft.	10   Monitoring well
2 Irrigation 4 Industrial 7 Lawn and garden (domes was a chemical/bacteriological sample submitted to Department submitted  TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify be 2 PVC 4 ABS 7 Fiberglass  lank casing diameter 2 in. to 70 ft., Dia in. to asing height above land surface 0 in., weight 0.703 lbs./  YPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS in CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 3 Mill slot 6 Wire wrapped 2 Louvered shutter 4 Key punched 7 Torch cut in the continuous slot 5 From 70 ft. to 80 ft. From 6 ft. to	10   Monitoring well
Was a chemical/bacteriological sample submitted to Department submitted  TYPE OF BLANK CASING USED:  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify be 2 PVC 4 ABS 7 Fiberglass  lank casing diameter 2 in. to 70 ft., Dia in. to asing height above land surface 0 in., weight 0.703 lbs./  YPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS  CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped  1 Continuous slot 3 Mill slot 6 Wire wrapped  2 Louvered shutter 4 Key punched 7 Torch cut  CREEN-PERFORATED INTERVALS: From 70 ft. to 80 ft  From ft. to 68 ft. to 60 ft	# Yes No X If yes, mo/day/yr sample was Vater Well Disinfected? Yes No X    CASING JOINTS: Glued   Clamped
TYPE OF BLANK CASING USED:  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify be 2 PVC 4 ABS 7 Fiberglass  lank casing diameter 2 in. to 70 ft., Dia in. to asing height above land surface 0 in., weight 0.703 lbs./  YPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 3 Mill slot 6 Wire wrapped 2 Louvered shutter 4 Key punched 7 Torch cut 1 CREEN-PERFORATED INTERVALS: From 70 ft. to 80 ft. From 68 ft. to 60 ft. to	CASING JOINTS: Glued Clamped  Welded  Threaded Flush  ft., Dia in. to ft.  Wall thickness or gauge No. SCH. 40  10 Asbestos-cement  11 Other (specify)  12 None used (open hole)  8 Saw cut 11 None (open hole)  9 Drilled holes
TYPE OF BLANK CASING USED:  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify be 2 PVC 4 ABS 7 Fiberglass  lank casing diameter 2 in. to 70 ft., Dia in. to asing height above land surface 0 in., weight 0.703 lbs./  YPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS  CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped  1 Continuous slot 3 Mill slot 6 Wire wrapped  2 Louvered shutter 4 Key punched 7 Torch cut  CREEN-PERFORATED INTERVALS: From 70 ft. to 80 ft.  From ft. to 50 ft. to 60 ft.	CASING JOINTS: Glued Clamped  Weided  Threaded Flush  ft., Dia in. to ft.  Wall thickness or gauge No. SCH. 40  10 Asbestos-cement  11 Other (specify)  12 None used (open hole)  8 Saw cut 11 None (open hole)  9 Drilled holes
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify be 2 PVC 4 ABS 7 Fiberglass  lank casing diameter 2 in. to 70 ft., Dia in. to asing height above land surface 0 in., weight 0.703 lbs./  YPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 3 Mill slot 6 Wire wrapped 2 Louvered shutter 4 Key punched 7 Torch cut CREEN-PERFORATED INTERVALS: From 70 ft. to 80 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 68 ft. to 80 ft.	How) Welded Threaded Flush  ft., Dia in. to ft.  M. Wall thickness or gauge No. SCH. 40  10 Asbestos-cement 11 Other (specify) 12 None used (open hole) 8 Saw cut 11 None (open hole) 9 Drilled holes
2 PVC	Threaded Flush  ft., Dia in. to ft.  Wall thickness or gauge No. SCH. 40  10 Asbestos-cement  11 Other (specify)  12 None used (open hole)  8 Saw cut 11 None (open hole)  9 Drilled holes
Iank casing diameter	ft., Dia in. to ft.  It. Wall thickness or gauge No. SCH. 40  10 Asbestos-cement  11 Other (specify)  12 None used (open hole)  8 Saw cut 11 None (open hole)  9 Drilled holes
asing height above land surface	ft. Wall thickness or gauge No. SCH. 40  10 Asbestos-cement  11 Other (specify)  12 None used (open hole)  8 Saw cut  11 None (open hole)  9 Drilled holes
1   Steel   3   Stainless steel   5   Fiberglass   8   RMP (SR 2   Brass   4   Galvanized steel   6   Concrete tile   9   ABS	11 Other (specify) 12 None used (open hole) 8 Saw cut 11 None (open hole) 9 Drilled holes
1   Steel   3   Stainless steel   5   Fiberglass   8   RMP (SR 2   Brass   4   Galvanized steel   6   Concrete tile   9   ABS	11 Other (specify) 12 None used (open hole) 8 Saw cut 11 None (open hole) 9 Drilled holes
2 Brass       4 Galvanized steel       6 Concrete tile       9 ABS         CREEN OR PERFORATION OPENINGS ARE:       5 Gauzed wrapped         1 Continuous slot       3 Mill slot       6 Wire wrapped         2 Louvered shutter       4 Key punched       7 Torch cut         CREEN-PERFORATED INTERVALS:       From       ft. to       80       ft         From       ft. to       ft. to       ft         GRAVEL PACK INTERVALS:       From       68       ft. to       80       ft	12 None used (open hole) 8 Saw cut 11 None (open hole) 9 Drilled holes
1 Continuous slot         3 Mill slot         6 Wire wrapped           2 Louvered shutter         4 Key punched         7 Torch cut           CREEN-PERFORATED INTERVALS:         From         70 ft. to         80 ft           From         ft. to         ft. to         80 ft           GRAVEL PACK INTERVALS:         From         68 ft. to         80 ft	9 Drilled holes
1 Continuous slot         3 Mill slot         6 Wire wrapped           2 Louvered shutter         4 Key punched         7 Torch cut           CREEN-PERFORATED INTERVALS: From 70 ft. to 80 ft           From ft. to 68         ft. to 80 ft           GRAVEL PACK INTERVALS: From 68 ft. to 80 ft	9 Drilled holes
2 Louvered shutter         4 Key punched         7 Torch cut           CREEN-PERFORATED INTERVALS:         From         ft. to         80         ft           From         ft. to         ft         to         ft           GRAVEL PACK INTERVALS:         From         68         ft. to         80         ft	
CREEN-PERFORATED INTERVALS:         From         70         ft. to         80         ft           From         ft. to         ft. to         ft           GRAVEL PACK INTERVALS:         From         68         ft. to         80         ft	TO Other (Specify)
From ft. to ft  GRAVEL PACK INTERVALS: From <b>68</b> ft. to <b>80</b> ft	There is a second of the secon
GRAVEL PACK INTERVALS: From 68 ft. to 80 ft	From # 4 to #
	From # to #
FION II. 10	# # # # # # # # # # # # # # # # # # #
	1.30
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite	4: Other
nout medvas from	
ANTICLE OF THE CONTROL OF THE PROPERTY OF THE CONTROL OF THE CONTR	restock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fu 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fe	rtilizer storage 16 Other (specify below)
	ecticide storage
the control of the co	iny feet?
FROM TO CODE LITHOLOGIC LOG FROM TO	PLUGGING INTERVALS
0 3 Topsoil, clay, with roots	
3 48 Clay, brown, silty	
48 60 Shale, olive	<u>ar þegna eigstið staga ar menna skiletikanska þaraðalandina er hannaðalandi</u>
60 80 Lithology not logged	
<del>angangan kananan kanan</del>	
<del>and the first the second and the second transfer and the second transfer to the second second second second second</del>	
	<u>and the province of the state </u>
	GPS:
	Latitude: N 38.596792
	Longitude: W 97.062475
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) r	the state of the s
00/41/12	i econstructed, or (3) plugged under my jurisdiction and was
completed on (mo/day/yr) and this record	is true to the best of my knowledge and belief. Kansas
completed on (mo/day/yr)  Water Well Contractor's License No.  531  This Water Well	is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 531 This Water Wel	is true to the best of my knowledge and belief. Kansas Record was completed on (mo/day/yr) 10/15/13