MW-09

WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WELL: County: Marion	Fraction SW ¼ SW ¼ (حداله ¼	Section Number Township No. Range Number T 17 S R 3 ZE W
Street/Rural Address of Well Location; if unknown, distance & direction G		Global Positioning System (GPS) information:
from nearest town or intersection: If at owner's address, check here . Latitude: .38,59615		
110 F Street		Longitude: 97.05895 (in decimal degrees)
Ramona, KS 67475		Elevation:
2 WATER WELL OWNER: USDA/O	CCC Farm Service Agency	Collection Method:
RR#, Street Address, Box #: 1400 Independence Ave SW		GPS unit (Make/Model: iPhone 4
City, State, ZIP Code Washing	gton. DC 20250-0513	☐ Digital Map/Photo, ☐ Topographic Map. ☐ Land Survey Est. Accuracy: ☐ <3 m. ☐ 3-5 m. ☐ 5-15 m. ☐ >15 m.
3 LOCATE WELL	COMPLETED WELL 55	۵
		ft. (2) ft. (3) ft.
N WELL'S STATI	IC WATER LEVEL 54.23	below land surface measured on mo/day/yr12/19/13
Pump	lest data: Well water was	ft. after
NW NI D II IN		it. andin. to
WELL WATER	TO BE USED AS: Public wat	er supply Geothermal Injection well
Domestic .		er supply Dewatering Other (Specify below)
Irrigation	☐ Industrial ☐ Domestic-lay	vn & garden Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes No		
8 If yes, mo/day/yr sample was submitted		
Water well disinfected? Yes No		
5 TYPE OF CASING USED: Steel PVC Other		
CASING JOINTS: Glued Clamped Welded Threaded		
Casing diameter 1.0 in to 45.0 ft. Diameter in to ft. Diameter in to ft.		
Casing height above land surface6		
Steel Stainless Steel PVC Other (Specify)		
Brass Galvanized Steel None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:		
Continuous slot Mill slot Gauze wrapped Forch cut Drilled holes None (open hole) Louvered shutter Key punched Wire wrapped Saw cut Other (specify)		
SCREEN-PERFORATED INTERVALS: From 45.0 ft to 55.0 ft., From ft. to ft.		
From ft. from ft. from ft. ft. to ft.		
From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 44.0 ft. ft. to 55.0 ft., From ft. to ft. From 42.0 ft. to 55.0 ft., From ft. to ft.		
From. 42.0% ft. to . 5.5.c.O ft., From ft. to ft.		
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other		
Grout Intervals: From 2.0 ft. to 42. ft., From ft. to ft., From ft. to ft.		
What is the nearest source of possible contamination: ☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)		
Sewer times Cesspool	Sewage lagoon Fuel storag	c Abandoned water well
☐ Watertight sewer lines ☐ Scepage p	oit Feedyard Fertilizer st	
Direction from well 200' East		from well
FROM TO LITHOLOG	GIC LOG FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS
O HO TILL	The Control of the Co	The state of the s
40 45 Sand & Cla	4	
	The state of the s	
A DECEMBER OF THE PROPERTY OF		A STATE OF THE PROPERTY OF THE
	NAMES OF STREET AND ADDRESS OF STREET ADDRESS OF STREET ADDRESS OF STREET AND ADDRESS OF STREET AND ADDRESS OF STREET ADDRESS OF STR	
TOWER ACTOR'S OR LANDOWNER	PS CEDIFICATION: This water	er well was 🗸 constructed 🖂 reconstructed or 🦳 plugged
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 12/18/2013 and this record is true to the best of my knowledge and belief.		
Kansas Water Well Contractor's License No. (480, This Water Well Record was completed on (methany/year) 4/15./14		
under the business name of Delta Environe Atal by (signature) by		
INSTRUCTIONS Use typewriter or bail point pen PLEASE PRESS FIRMLY and PRINT clearly Please fill in blanks and check the offect payers. Send one copy to		
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW, Jackson St., Suite 420, Topeka, Kansas of 12-1367. Exceptione 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at		