

1 LOCATION OF WATER WELL: County: Osage	Fraction NE ¼ NE ¼ SE ¼	Section Number 31	Township Number T 18 S	Range Number R 16 EW
--	----------------------------	----------------------	---------------------------	-------------------------

Distance and direction from nearest town or city street address of well if located within city?  
1½ south, 2¼ west of Melvern

2 WATER WELL OWNER: Don Tobler  
RR#, St. Address, Box #: 2711 Lynx Road NW  
City, State, ZIP Code: Lebo, KS 66856  
Board of Agriculture, Division of Water Resources  
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 100' ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1. 10' ft. 2. ft. 3. ft.  
 WELL'S STATIC WATER LEVEL 6' ft. below land surface measured on mo/day/yr 10-01-93  
 Pump test data: Well water was ft. after hours pumping gpm  
 Est. Yield 20 galons per hour Well water was ft. after hours pumping gpm  
 Bore Hole Diameter 8 3/4 in. to ft. and in. to ft.  
 WELL WATER TO BE USED AS:  
 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 5 Public water supply 6 Oil field water supply 7 Lawn and garden only 8 Air conditioning 9 Dewatering 10 Monitoring well 11 Injection well 12 Other (Specify below)  
 Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:  
 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below)  
 Blank casing diameter 5" in. to 0-10 ft., Dia 5" in. to 20-100 ft., Dia in. to ft.  
 Casing height above land surface 24" in., weight 2.82 lbs./ft. Wall thickness or gauge No. 258  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 11 None (open hole)  
 SCREEN-PERFORATED INTERVALS: From 10 ft. to 20 ft., From ft. to ft.  
 GRAVEL PACK INTERVALS: From 9 ft. to 100 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 0 ft. to 9 ft., From ft. to ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) creek  
 Direction from well? west How many feet? 50'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	8	Clay-Brown			
8	10	Limestone-Grey			10-12-93 Permission to shallow grout from Don Taylor
10	22	Shale-Grey			
22	23	Limestone-Grey			
23	24	Shale-Grey			
24	38	Limestone-Grey			
38	42	Shale-Grey			
42	66	Limestone-Grey			
66	69	Shale-Grey			
69	70	Limestone-Grey			
70	75	Shale-Grey			
75	93	Limestone-Grey			
93	105	Shale-Grey			
105	110	SANDstone-Grey			
110	180	Shale-Grey			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-01-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/yr) 11-16-93 under the business name of STRADER DRILLING CO., INC. by (signature) Dale Becken

OFFICE USE ONLY