	-		WATE	R WELL RECORD F	orm WWC-5	KSA 8	2a-1212		
_	ON OF WAT FRANKLI		Fraction 5£ 1/4	SE 1/4 NW	i	tion Number 2	T Township Number	Range Number	
Distance a	nd direction	from nearest tov		address of well if located $2N/2$	within city?	e Wil	liams burg		
2 WATER	WELL OW	NER: Ste	eve Wilcoxs				TAMS DUTY		
<b>→</b>	ddress, Box		2 Box 17			Board of Agriculture, Division of Water Resources			
City, State, ZIP Code : Pomona, KS 66076					Application Number:				
LOCATE WELL'S LOCATION WITH A DEPTH OF COMPLETED WELL. 200 ft. ELEVATION:  Depth(s) Groundwater Encountered 1 140-160 ft. 2 160-180 ft. 3.  WELL'S STATIC WATER LEVEL 142 ft. below land surface measured on mo/day/yr 2-15-88.  Pump test data: Well water was ft. after hours pumping									
Est. Yield gpm: Well water was ft. after hours pumping gpm									
<u>•</u> w ⊢	<u> </u>		Bore Hole Diam	eter8in. to.		ft.	, and	in. to	
₹ "	!!	! [ ]	WELL WATER	TO BE USED AS: 5	Public water	er supply	8 Air conditioning	11 Injection well	
īL	_ swl	\$ <del>-</del>	1 Domestic	3 Feedlot 6	Oil field wa	iter supply	9 Dewatering	12 Other (Specify below)	
1 1	1	ī	2 Irrigation		•		10 Observation well		
Į L	<u> </u>		Was a chemical mitted	bacteriological sample su	ibmitted to D		YesNoX; It Vater Well Disinfected? Ye	f yes, mo/day/yr sample was sub- es X No	
5 TYPE C	F BLANK C	CASING USED:		5 Wrought iron	8 Concre	ete tile	CASING JOINTS:	Glued . X Clamped	
1 Ste	el	3 RMP (S	R)	6 Asbestos-Cement	9 Other	(specify bel	ow)	Welded	
2 PV		4 ABS		7 Fiberglass				Threaded	
								in. to ft.	
Casing height above land surface24"in., weight2.82									
TYPE OF	SCREEN O	R PERFORATIO	N MATERIAL:		_ 7 PV	<u>'C</u>	10 Asbestos-	cement	
1 Steel 3 Stainless steel				5 Fiberglass 8 R		MP (SR)	P (SR) 11 Other (specify)		
2 Bra	ISS	4 Galvaniz	zed steel	6 Concrete tile	e 9 ABS 1		12 None use		
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From									
From									
			From	ft. to		ft., F	rom	ft. to ft.	
6 GROUT	MATERIAL	.: 1 Neat	cement	2 Cement grout	3 Bento	onite	4 Other		
Grout Intervals: From									
What is the	nearest so	ource of possible	contamination:			10 Livestock pens		14 Abandoned water well	
1 Septic tank 4 Latera			ral lines	7 Pit privy		11 Fuel storage 15 Oil w		15 Oil well/Gas well	
2 Sewer lines 5 Cess			pool	8 Sewage lagoon		12 Fertilizer storage		16 Other (specify below)	
	-	er lines 6 Seep	page pit	9 Feedyard		13 Insecticide storage			
	om well? /	JW					any feet? //O		
FROM	то		LITHOLOGIC	LOG	FROM	то		DLOGIC LOG	
0-	1	Top Soil			89	100_	Sandstone-Grey		
1	4	Clay-Bro			100	110	Limestone-Grey		
4	10		e-Yellow		110	120	Shale-Black		
10	14	Shale-Gr	-		120	135	Shale-Grey		
14	16		e-Grey		135-1	1	Sandstone-Grey		
16	23	_	rey		184	187	Limestone-Grey		
23	26		e-Grey		187	200	Shale-Grey		
26	29	Shale-Gr	-						
29	35		e-Tan		1				
35	46	Shale-Gr							
46	65	Limeston	e-Grey			<del> </del>			
65	73	Shale-Bl							
73	76	Limeston	-						
76	87	Sandston							
87 89 Limestone-Grey									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was									
completed on (mo/day/year)2-15-88									
					II Hecord wa				
				Co., Inc.	v. Please fill in	blanks under	nature) July 1	s. Send top three copies to Kansas	
								L OWNER and retain one for your	