


1 LOCATION OF WATER WELL: County: Franklin Fraction: 1/4 NE Section Number: 6 Township Number: T 18 S Range Number: R 18 E

Distance and direction from nearest town or city street address of well if located within city?
2 1/2 North 1/2 East

2 WATER WELL OWNER: City of Williamburg well #7
RR#, St. Address, Box #
City, State, ZIP Code: Williamburg, Ky 66095
Board of Agriculture, Division of Water Resources
Application Number: 35548

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 210 ft. ELEVATION: 141 ft.
Depth(s) Groundwater Encountered 1. 141 ft. 2. 99 ft. 3. July 1388 ft.
WELL'S STATIC WATER LEVEL 99 ft. below land surface measured on mo/day/yr
Pump test data: Well water was 19 gpm: Well water was 10 ft. after 210 hours pumping 1388 gpm
Est. Yield 19 gpm: Well water was 10 ft. after 210 hours pumping 1388 gpm
Bore Hole Diameter 10 in. to 210 ft. and 210 in. to 210 ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
Was a chemical/bacteriological sample submitted to Department? Yes No.....; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
7 Fiberglass Threaded
Blank casing diameter 6 1/4 in. to 141 ft., Dia 36 in. to 210 ft., Dia 235 in. to 210 ft.
Casing height above land surface 36 in., weight 235 lbs./ft. Wall thickness or gauge No. 235
TYPE OF SCREEN OR PERFORATION MATERIAL: Steel 7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
7 Torch cut
SCREEN-PERFORATED INTERVALS: From 141 ft. to 200 ft., From 200 ft. to 210 ft.
GRAVEL PACK INTERVALS: From 51 ft. to 210 ft., From 210 ft. to 210 ft.

6 GROUT MATERIAL: Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 51 ft. to 210 ft., From 210 ft. to 210 ft.
What is the nearest source of possible contamination: None
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
In Pasture
Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	5	Soil			
5	13	Yellow Rock			
13	19	Black Shald			
19	24	Lime			
24	43	Light Shald			
43	51	Lime			
51	62	Shald			
62	64	Lime			
64	79	Shald			
79	90	Lime			
90	105	grey Sanded Shald			
105	111	Lime			
111	141	grey Sanded Shald			
141	200	White Sand			
200	210	Shald			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) July 13 81 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 351 This Water Well Record was completed on (mo/day/yr) 7/4/82 under the business name of Royce Swank Drilling by (signature) Royce Swank
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.