

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Franklin	NE ¼ SE ¼ SW ¼	6	T 18 S	R 18E E/W

Distance and direction from nearest town or city street address of well if located within city?

1 3/4 miles north of Williamsburg**permit # 05 WW Fr 15**

2 WATER WELL OWNER: William M Kuyma	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : 1778 California Terrace	Application Number:
City, State, ZIP Code : Pomona, Ks. 66076	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 215 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 15.6 ft. below land surface measured on mo/day/yr 11-17-05 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 1.5 gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5 in. to ft., Dia in. to ft., Dia in. to ft., Dia	Threaded
Casing height above land surface 24 in., weight 2.82 lbs./ft. Wall thickness or gauge No. 2.58			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-Cement	
1 Steel	3 Stainless Steel	8 RMP (SR)	11 Other (Specify)
2 Brass	4 Galvanized Steel	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	5 Guazed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify) ft.
SCREEN-PERFORATED INTERVALS: From 160 ft. to 190 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 140 ft. to 215 ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 4 ft. to 24 ft., From 120 ft. to 140 ft., From ft. to ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well? south				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below) lagoon
				How many feet? 350

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	top soil	82	103	limestone grey
2	4	clay brown	103	111	shale grey limy
4	6	limestone yellow	111	112	coal
6	7	shale brown	112	124	shale grey
7	14	limestone grey	124	149	shale grey sandy
14	18	shale black	149	189	sandstone grey
18	20	limestone grey	189	207	
20	41	shale grey	189	207	shale grey
41	45	limestone grey	207	209	limestone grey
45	79	shale grey	209	213	shale grey
79	61	limestone grey	213	215	limestone grey
61	64	shale blue grey			
64	81	shale grey			
81	82	coal			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-17-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 182 This Water Well Record was completed on (mo/day/yr) 12-29-05 under the business name of Strader Drilling Co., Inc. by (signature) <i>[Signature]</i>
--