

1 LOCATION OF WATER WELL: County: Miami	Fraction NW ¼ SE ¼ SW ¼	Section Number 11	Township Number T 18 S	Range Number R 22	<u>EW</u>
--	----------------------------	----------------------	---------------------------	----------------------	-----------

Distance and direction from nearest town or city street address of well if located within city?
820 South Sixth Street, Osawatomie, Kansas 66064

2 WATER WELL OWNER: E.K. Campbell Co.
 RR#, St. Address, Box #: 820 South Sixth Street
 City, State, ZIP Code: Osawatomie, KS 66064
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 12 ft. ELEVATION: apx. 860' MSL
 Depth(s) Groundwater Encountered 1. 2.90 ft. 2. . ft. 3. . ft.
 WELL'S STATIC WATER LEVEL 2.90 ft. below land surface measured on mo/day/yr 04/18/95
 Pump test data: Well water was . ft. after . hours pumping . gpm
 Est. Yield . gpm: Well water was . ft. after . hours pumping . gpm
 Bore Hole Diameter . 8 in. to TD . ft., and . in. to . ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well MW-6
 Was a chemical/bacteriological sample submitted to Department? Yes. . No. X .; If yes, mo/day/yr sample was submitted .
 Water Well Disinfected? Yes . No .

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued . Clamped .
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded .
 7 Fiberglass . Threaded . X .
 Blank casing diameter . 2 in. to . 2 ft., Dia . in. to . ft., Dia . in. to . ft.
 Casing height above land surface . 1.33 ft. in., weight . lbs./ft. Wall thickness or gauge No Scheduled 40 .
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) .
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) .
 SCREEN-PERFORATED INTERVALS: From . 12 ft. to . 2 ft., From . ft. to . ft.
 From . ft. to . ft., From . ft. to . ft.
 GRAVEL PACK INTERVALS: From . 12 ft. to . 1.5 ft., From . ft. to . ft.
 From . ft. to . ft., From . ft. to . ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other .
 Grout Intervals: From . 1.5 ft. to . 0 ft., From . ft. to . ft., From . ft. to . ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? East How many feet? 300

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5'	fill: sand, gravel			
5'	12'	dark gray to brown, stiff, moist silty clay (CL)			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) . 04/17/95 . and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 568 . This Water Well Record was completed on (mo/day/yr) 4-18-95 under the business name of MAX'S Enterprises by (signature) David Hurych