WATER WELL RECORD	Form WWC-5	Division of Wate	r Resources App. N	o. 21,546	
1 LOCATION OF WATER WELL:	Fraction	Section Number	Township No.	Range Number	
County: Kearny	1/4 lot1 1/4 NE 1/4 NE 1/4		T 26 S	R 36 □E 🗹 W	
Street/Rural Address of Well Location;	Global Positioning				
from nearest town or intersection: If at owner's address, check here .				(in decimal degrees)	
S.side of Lakin,1 mile S.,1/4 mile E. to Lakin Ln.,6 miles S.,1 3/4		Longitude: (in decimal degrees)			
mile E.,1 1/3mile S. 4312' N. 1160' W.		Elevation:			
2 WATER WELL OWNER: TFT Alfalfa Farms Well # T15		Collection Method:			
RR#, Street Address, Box #: 1320 N. County Rd. 11		GPS unit (Make/Model:)			
City, State, ZIP Code : Leoti, KS. 67861		Digital Map/Photo, Topographic Map, Land Survey			
Est. Accuracy:					
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 415					
N WELL'S STATE	WELL'S STATIC WATER LEVEL. 228ft. below land surface measured on mo/day/yr. 8-19-10				
	Pump test data: Well water wasft. after hours pumping gpm				
EST. YIELDgpm. Well water wasft. after hours pumpinggpm					
W E Bore Hole Diameter 20					
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)					
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below) I					
Was a chemical/bacteriological sample submitted to Department? Yes V No					
S If yes, mo/day/yr sample was submitted					
1 mile Water well disinfected? ☐ Yes ☑ No					
5 TYPE OF CASING USED: Steel PVC Other					
CASING JOINTS: Glued Clamped Welded Threaded					
Casing diameter .16. in to .235. ft., Diameter in to ft., Diameter in to ft.					
Casing height above land surface12	in., Weight 42.05	lbs./ft., Wall this	ckness or gauge N	o250	
TYPE OF SCREEN OR PERFORATION MATERIAL:					
✓ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)					
SCREEN OR PERFORATION OPENINGS ARE:					
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)					
☐ Louvered shutter ☐ Key punched ☑ Wire wrapped ☐ Saw cut ☐ Other (specify)					
SCREEN-PERFORATED INTERVALS: From					
From					
From					
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other					
Grout Intervals: From 0 ft. to 20 ft., From 160 ft. to 220 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)					
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well					
Direction from well		from well		***************************************	
FROM TO LITHOLOG				JGGING INTERVALS	
			·		
See Attached Log					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged					
under my jurisdiction and was completed on (mo/day/year) .8-19-10 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/year)					
under the business name of Minter Wilson Drilling Co. Inc. by (signature) Cada Bakker.					
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies					
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296,5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at					
http://www.kdheks.gov/waterwell/index.html.					
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy					

21,546

MINTER-WILSON DRILLING CO. Water Systems Complete Installation

Irrigation and Domestic and Repairing

INCORPORATED

P.O. Box A . GARDEN CITY, KANSAS 67846 Phone 620-276-8269

NAME

BRENT TOKOL

COUNTY

KEARNY

DATE

7-16-10

LOCATION:

NE 1/4 2-26-36 - FROM LAKIN LANE & PARALLEL ROAD -

1-1/4 MILES EAST, 5/8THS MILE SOUTH

& 1/4 MILE EAST

- 30 FT. SOUTH OF 3RD WHEEL TRACK FROM THE NORTH EDGE OF CIRCLE

STATIC WATER LEVEL - 210 FT.

TEST # 5

0' TO 2' - FINE SAND

2' TO 8' - BROWN SANDY CLAY

8' TO 162' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE WITH LAYERS OF BROWN CLAY

162' TO 169' - BROWN SANDY CLAY

169' TO 178' - BROWN & BLUE CLAY

178' TO 184' - FINE TO MEDIUM SAND & GRAVEL

184' TO 197' - BROWN & BLUE CLAY

197' TO 213' - FINE TO MEDIUM SAND & GRAVEL

213' TO 224' - BROWN SANDY CLAY WITH STRIPS OF GRAVEL - TIGHT

224' TO 244' - FINE TO MEDIUM SAND & GRAVEL

244' TO 283' - BROWN SANDY CLAY

283' TO 287' - FINE TO MEDIUM SAND

287' TO 293' - BROWN SANDY CLAY

293' TO 304' - FINE TO MEDIUM SAND & GRAVEL

WITH LAYERS OF BROWN SANDY CLAY - 30%

304' TO 310' - BROWN SANDY CLAY

310' TO 336' - BROWN CLAY

336' TO 345' - FINE TO MEDIUM SAND & GRAVEL

345' TO 350' - BROWN CLAY

350' TO 359' - BROWN SANDY YELLOW & WHITE CLAY

WITH 25% BROWN ROCK - TIGHT

359' TO 364' - GOOD LOOSE BROWN ROCK - TOOK WATER

364' TO 366' - BROWN CLAY

366' TO 378' - BROWN, YELLOW & WHITE CLAY WITH 40% BROWN ROCK

378' TO 390' - BROWN, YELLOW & WHITE CLAY WITH 10% BROWN ROCK

390' TO 395' - SHALE