

1 LOCATION OF WATER WELL:	Fraction NW 1/4 NE 1/4 NE 1/4	Section Number 14	Township Number T 18 S	Range Number R 4 EW
---------------------------	--------------------------------------	--------------------------	-------------------------------	----------------------------

Distance and direction from nearest town or city street address of well if located within city?

Southeast corner of Hwy 56 and east Main Street -- Lincolnville, KS

2 WATER WELL OWNER: KDOT BUREAU OF DESIGN ENVIRONMENTAL SERVICES SECTION	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: DOKING STATE OFFICE Bldg.	Application Number:
City, State, ZIP Code: TOPEKA, KS 66612	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 30.0 ft. ELEVATION:
--	--

Depth(s) Groundwater Encountered ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL **12.0** ft. below land surface measured on mo/day/yr **10-24-03**

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	6 Oil field water supply	8 Air conditioning	11 Injection well
2 Irrigation	4 Industrial	7 Domestic (lawn & garden)	9 Dewatering	12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No **X**.....; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No **XXXX**.....

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	Welded
2 PVC	4 ABS	7 Fiberglass	Threaded X
Blank casing diameter 2 in. to 10.0 ft., Dia	in. to ft., Dia in. to ft.		
Casing height above land surface below 2 in., weight	lbs./ft. Wall thickness or gauge No. Sch 40		
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless Steel	5 Fiberglass	7 PVC
2 Brass	4 Galvanized Steel	6 Concrete tile	8 RMP (SR)
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	8 Saw cut
1 Continuous slot	3 Mill slot - .010	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	11 None (open hole)
SCREEN-PERFORATED INTERVALS:		From 30.0 ft. to 10.0 ft., From ft. to ft.	
GRAVEL PACK INTERVALS:		From 30.0 ft. to 9.0 ft., From ft. to ft.	

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 9.0 ft. to 0.0 ft., From ft. to ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? West			13 Insecticide storage	Highway runoff
			How many feet? 10	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3.0	Backfill	30.0	9.0	10/20 Sand
3.0	8.0	Tan clay	9.0	0.0	Bentonite Chips
8.0	20.0	Gray clay/shale			
20.0	28.0	Dark Brn/black clay			
28.0	30.0	Limestone			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1) constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/14/03 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 665 This Water Well Record was completed on (mo/day/yr) 11/03/03 under the business name of Pratt Well Environmental by (signature) <i>Steven Egel</i>
--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.