		WATER W	VELL RECORD	Form WWC-	5 KSA 82	a-1212			
1 LOCATION C	OF WATER WELL:	Fraction 4	G . C	Se,	ction Number	Townshin	`lumber S	Range	Number E/W
	irection from nearest town		ess of well if locate	d within city?		<u> </u>	103	<u> </u>	
24	W/ 17	A / 1	oln ville		6850	\boldsymbol{arrho}			
2 WATER WE						· · · · · · · · · · · · · · · · · · ·			
_	11006	ert Wint				Deced a	.6. 4	Divinion of MA	atas Dagger
RR#, St. Addre	18 7 77 8		Va				of Agriculture, I	JIVISION OF W	ater Hesourc
City, State, ZIP	Code : Lin C	olnville	<i>D</i> 8'	71			tion Number:		
J LOCATE WE	ELL'S LOCATION WITH 4	DEPTH OF COM	PLETED WELL	13/2	, . ft. ELEV	ATION:			
7.1.7. 11.0.		Depth(s) Groundwate							125 73th
ī !	! ! \\	WELL'S STATIC WA	ATER LEVEL . 🚅	> / ft. b	elow land su	ırface measured	on mo/day/yr	3.7./	7 7/
	W _ NE		şt data: Well wate						
	W E	Est. Yield ろ . 🟉	. அறரா: Well wate	r was	ft. :	after	hours pu	mping	gp
<u>•</u>		Bore Hole Diameter.							
ž w	· · · ·	WELL WATER TO B	BE USED AS:	5 Public water	er supply	8 Air condition	ing 11	Injection well	l
7 '		1 Domestic	3 Feedlot	6 Oil field wa	iter supply	9 Dewatering	12	Other (Speci	fy below)
5	W SE	2 Irrigation	4 Industrial	7 Lawn and	garden only	10 Monitoring y	vell		
1 1		Was a chemical/bacte				•			
1		nitted	onological campio c			ater Well Disinfe		∠ No	ampio mas or
5 TYPE OF BI	LANK CASING USED:		Wrought iron	8 Concr			JOINTS: Glued	17	mned
1 Steel	3 RMP (SR)		•					•	•
	` '		Asbestos-Cement	9 Other	(specify belo	w)		ed	
2 PVC	4 ABS		Fiberglass					aded	
_	ameter ir		ft., Dia	∵' ი' ი ზ	120	ft., Dia		in. to	1
	bove land surface		weight . C./a	アルプン	. <i>O. U</i> Ibs.	ft. Wall thicknes	ss or gauge N	o. 1 ~	y
TYPE OF SCRI	EEN OR PERFORATION	MATERIAL:		7 PV		10 /	Asbestos-ceme	ent	
1 Steel	3 Stainless	steel 5	Fiberglass	8 RN	IP (SR)	11 (Other (specify)		
2 Brass	4 Galvanize	d steel 6	Concrete tile	9 AB	S	12 1	None used (op	en hole)	
SCREEN OR P	ERFORATION OPENING	S ARE:	5 Gauze	ed wrapped		8 Saw cut	_	11 None (c	pen hole)
1 Continu	ous slot 3 Mill	slot	6 Wire	wrapped		9 Drilled hole	es		
2 Louvere	ed shutter 4 Key	punched	7 Torch			10 Other (spe	cify)		
SCREEN-PERF	ORATED INTERVALS:	From		• • • • •	ft. Fro	om	• -		
		From				om			
GRAV	'EL PACK INTERVALS:	From 2.4	ft. to						
		From	ft. to		ft., Fro		ft. to		1
GROUT MAT	TERIAL: 11 Neat ce		ement grout	3 Rento		Other			
Grout Intervals:	4/	2/1	. ft., From						
	arest source of possible of	- /	. it., Tioin			•		bandoned wa	
1 Septic to	•		7 Dit orige		***************************************	stock pens			
_ •			7 Pit privy		11 Fuel	•		il well/Gas w	
2 Sewer li	•		8 Sewage lago	oon		lizer storage	16 U	ther (specify	below)
_	tht sewer lines 6 Seepag	ge pit	9 Feedyard			cticide storage	/ · · · · · · · · ·		
Direction from v		LITHOLOGIC LOS		T ====	·	iny feet?	<u> </u>)TED! (4) 0	
	0 0	LITHOLOGIC LOG	<u>i </u>	FROM	то		PLUGGING II	VIERVALS	
0 1	0 Clay								
, ,	, la ,	α			ļ				
10 2	Mixed	Shales	Lhime						
				1					
21 4	4 Yellon	1 & Bray	Clay	Mixe	2 20	0-10			
			7						
49 6	4 81110	Shale							
	1 2100								
64 6	5 Wate	<u> </u>							
		<u></u>							
65 7	5 Blue S	76-1-		 			<u>-</u>		
	2 DIVE 2	1018							
									,
CONTRACT	OR'S OR LANDOWNER'S	S CERTIFICATION:	This water well we	as (1) constru	cted (2) rece	onstructed or (3) plugged und	er mv iurisdi	ction and wa
		12-0	To water well we	AS (1) CONSILU					
completed on (n	• • •	170	#	-		ord is true to the	Design iny kno	A Carlo	Delle I. Marisa
	tractor's License No	Khun T	inis water W	ell mecora wa	-	on (mo/day/yr)	1001		10
	ess name of Pac	BHUS	101/11/10	9	by (signa		W 14.	Jus	me
	IS: Use typewriter or bail point pe Environment, Bureau of Water, To								Department
oi neaith and	Environment, Dureau Of Water, 10	Juna, nalisas 00020-7320	o. 100phone. 313-230-30			and retain Of	,001 1600108	•	