1 LOCATIO	ON OF WATE	D WELL:	Fraction	ATER WELL REC	ORD For		KSA 82a-		er Range N	lumber
County:		arion	NW 3	4 NW 1	NE		14	40	1 -	. 1
Distance an			vn or city street	address of well				1 10	S R 4	
				SE 1 st Stree	t and Ma	in, Lincol	nville, Ks	3		
			roducts, In							
RR#, St. Ad	ldress, Box #	: C/O S	CS Engine	ers					re, Division of Water	Resources
City, State,	ZIP Code	: 10975	El Monte S	Suite 100 Ov	erland l	Park, Ks		Application Number	er:	-
LOCATE	WELL'S LO	CATON WITH	4 5557110	E COMPLETED		24	5 A ELF	EVATION: ft. 2		
JAN "X" II	N SECTION E	SOX:	Depth(e) Grou	r COMPLETED	WELL	24.	9 π. ELE	EVATION:		
	N		WELL'S STA	TIC WATER LEV	ileieu i 1.5 _. Æi		helow land	ft. 2 surface measured on m		ru
			P	imp test data:	Moll water		DEIOW IAITU	Ft. after h	ours oumping	Gnm
T	X	·	Fet Vield	Gom:	Moli water	was		Ft. after h Ft. after h Ft. and	Hours pumping	Gpm
-	NW	NE	Bore Hole Dis	meter 8.625	In to	24	5	Ft and	in to	Opin
₩L			WELL WATE	R TO BE USED	ĀŠ: 5 Pi	iblic water su	upply	8 Air conditioning	11 Injection we	Ft.
- " 「		-	1 Dome	stic 3 Feed lot	t 6 Oi	field water	supply	Ft. and 8 Air conditioning 9 Dewatering	12 Other (Spec	ify below)
	sw	SE	2 Irrigati	on 4 Industria	al 7 La	wn and gard	len (domes	tic) 10 Monitoring wel	<u> </u>	
	i	i	Was a chemic	al/bacteriologica	l sample si	ubmitted to [Department	? Yes No X	If yes, mo/day/yr sai	mple was
† <u>L</u>			Submitted	WEST CONTRACTOR			W	/ater Well Disinfected? `	Yes No	X
5 TYPE O	F BLANK CA	SING USED:		5 Wrough	t Iron	8 Concre	ete tile	CASING JOINTS:	GluedCla	mped
1 Ste	eel	3 RMP	(SR)	6 Asbesto	s-Cement	9 Other	(specify bel		Welded	
2 PV	c	4 ABS		7 Fibergla	ISS				Threaded	X
———	a diot	2	in to	Ft., 9.5 Dia				Ft., Dia	in to	
Siank casing	g diameter		in. to	Dia			0	ft. Wall thickness or gau	In. to	π.
			N MATERIAL:	in., weight _				10 Asbestos		
1 Ste				5 Fibergla	ee			11 Other (sp		
2 Bra				6 Concret		. 9	ABS	12 None use	ed (open hole)	
		TION OPENIN				d wrapped			11 None (op	en hole)
1 Co	ntinuous slot	3	Mill slot		6 Wire w	rapped		9 Drilled holes		
2 Lou	uvered shutte	r 4	Key punched		7 Torch	cut		10 Other (specify)		
SCREEN-P	ERFORATED	INTERVALS	: From	9.5 ft	. to			From	ft. to	ft.
			From	fi	i. to		ft.	From	ft. to	
SAI	ND PACK INT	ERVALS:	From	7.5 ft	i. to	24.5	ft.	From	ft. to	Ft.
			From	ft	. to			From	ft. to	Ft.
<u></u> GROUT	MATERIAL:	1 Neat	cement	2 Cement grou	<u>ıt</u>		tonite	4 Other		
Grout Inten	rale From 3	0	ft to 5	Ft. From2	5.5	Ft. 5 to	7	5 ft. From		i i
			contamination:					estock pens 1		
	ptic tank	c or possible	4 Lateral line		Pit privy				15 Oil well/ Gas well	
	wer lines		5 Cess pool		Sewage I	agoon		•	16 Other (specify be	
	atertight sewer	lines	6 Seepage		Feedyard	•		ecticide storage	Contaminate	
Direction fro			o coopago,		· oouyuno		How man	•		
FROM	то	CODE	LITH	OLOGIC LOG		FROM	то	1	ING INTERVALS	
0	1	Mi	llings and	gravel						
1	4	Sh	ale, weath	ered yellow						
4	5		mestone							
5	24		ale				ļ			
24	24.5			rème to tan			-			
24.5	TD	En	d of Boreh	iole		-	-			
				4100			 			
-						·			11-12	
7 CONTR	ACTOR'S OF		R'S CEDTIEIC	ATION: This use	or well wee	(v) construc	rted (2) res	constructed, or (3) plugge	ed under my juriedie	ion and w
_) 03/15/07	•		CI WEII WAS			true to the best of my kr		- 1
-	,			585				•	-	
		icense No.	Λοοοο	ated Enviro	nmente		ater Well H	Record was completed on By (signature) Bradi	ov I Johnson	, 13/0/
naer the bu	usiness name	ot ease fill in blank	s and circle the	correct answers	end three	nies to Kane	as Denartme	ent of Health and Environm	ent Bureau of Water	Topeka
				nd one to WATER					ent, Buleau of Water,	

Brook John