WATER WELL RECORD		Form WWC-5		Di	Division of Water Resources App. No.			
1 LOCATION OF WATER WELL: County: Marion		Fraction NW NE				Township No.		
Street/Rural Address o	f unknown, distance &			System (GPS)				
from nearest town or intersection: If at owner's address, check here								
—					Longitude: (in decimal degrees)			
					Elevation:			
				_ Datun	n: WGS 84	4, □ NAD 83, [☐ NAD 27	
2 WATER WELL OWNER: Steve Konark RR#, Street Address, Box #: City, State, ZIP Code : hincoln villeko					Collection Method:			
RR#, Street Address, Box #: 9 01 max: n					GPS unit (Make/Model:)			
City, State, ZIP Code : 1				☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey				
	hinc	oln ville-kc		Est. A	ccuracy: <	3 m, 🔲 3-5 m, [5-15 m, >15 m	
3 LOCATE WELL			Di					
WITH AN "X" IN	4 DEPTH OF	COMPLETED WEL	L <i>U.</i> ?.	<u>.</u>	ft.			
SECTION BOX:	Depth(s) Groundwater Encountered (1)							
N	WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr. 7							
Pump test data: Well water wasft. after hours pumping								
EST. YIELD. Well water was					ft. after hours pumping gpm			
W Bore Hole Diameter in to 95 in to 95					t., andft.			
			O BE USED AS: Public water supply Geothermal Injection well					
	Domestic	☐ Feedlot ☐	Oil field wa	ter suppl	v	watering [Other (Specify below)	
SW SE	☐ Irrigation							
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☐ No								
S If yes, mo/day/yr sample was submitted								
water well distillected?								
5 TYPE OF CASING USED: Steel Other								
CASING JOINTS:								
Casing diameter								
Casing diameter in. to ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface in., Weight _SDR lbs./ft., Wall thickness or gauge No2/4								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
Steel Stainless Steel PVC Other (Specify)								
			ole)		-1 3,			
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)								
SCREEN-PERFORATED INTERVALS: From 6.5 ft. to 6.5 ft. fr. from ft. to ft.								
From								
GRAVEL PACK INTERVALS: From ft. to ft. ft. from ft. to ft.								
From ft. to ft., From ft. to ft.								
From								
Grout Intervals: From								
What is the nearest source of possible contamination:								
Septic tank								
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well								
Watertight sewer lines Seepage pit Feedvard Fertilizer sto					Oil well/ga	ıs well		
Direction from well			. Distance	from we	ell <i>H.5</i>			
FROM TO	LITHOLOG	IC LOG	FROM	TO	LITHO. LO	OG (cont.) or PL	UGGING INTERVALS	
0 5 TOB	Seil							
JUP								
5 20 him	a Stone	2						
20 45 Veli	10411	Red Clay						
13 1211	TW T	iec c iny						
WX 65 400	d Blue S	16.10						
15 05 Far	<u> </u>	riare						
63 90 Kim	estone							
90 41 War	ter	3.4						
91 45 Har	d Gray S	shale			L	<u> </u>		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION; This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year)								
Kansas Water Well Contractor's License No								
under the business name of								
INSTRUCTIONS: Use typewi	riter or ball point pen	. PLEASE PRESS FIRML)	and PRINT c	learly. Ples	ase fill in blanks	and check the corr	ect answers. Send three copies	
(white, blue, pink) to Kansas D	Department of Health	and Environment, Bureau	of Water, Geo	logy Section	on, 1000 SW Jac	ckson St., Suite 420), Topeka, Kansas 66612-1367.	
Telephone 785-296-5524. Sen	d one copy to WAT	ER WELL OWNER and	retain one for	your recor	rds. Include fee	of \$5.00 for each	constructed well. Visit us at	
http://www.kdheks.gov/waterwe	II/index.html.		-					
KSA 82a-1212								