


1 LOCATION OF WATER WELL: Fraction NW 1/4 SW 1/4 SE 1/4 Section Number 1 Township Number T 18 S Range Number R 6E EW  
 County: Chase Distance and direction from nearest town or city street address of well if located within city?  
 2 1/2 mile NW of Hymer

2 WATER WELL OWNER: John Roviger  
 RR#, St. Address, Box #: Rt  
 City, State, ZIP Code: Burdick Ks 66838  
 Board of Agriculture, Division of Water Resources  
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:   
 4 DEPTH OF COMPLETED WELL: 55 ft. ELEVATION: 41 ft.  
 Depth(s) Groundwater Encountered 1. 15 ft. 2. 41 ft. 3. 55 ft.  
 WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr Feb 25 87  
 Pump test data: Well water was 3 gpm ft. after 43 ft. and 64 ft. in to 55 ft.  
 Est. Yield 3 gpm Well water was 43 ft. after 64 ft. hours pumping 55 gpm  
 Bore Hole Diameter 8 7/8 in. to 43 ft. and 64 ft. in to 55 ft.  
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well  
 Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped  
 2 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded  
 Blank casing diameter 5 in. to 40 ft. Dia. 16 in. to 55 ft. Dia. in. to 55 ft. Dia. in. to 55 ft. Dia.  
 Casing height above land surface 16 in. weight 16 lbs./ft. Wall thickness or gauge No. SDR-26  
 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)  
 SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 40 ft. to 55 ft. From 40 ft. to 55 ft. From 40 ft. to 55 ft.  
 GRAVEL PACK INTERVALS: From 13 ft. to 55 ft. From 13 ft. to 55 ft. From 13 ft. to 55 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 3 ft. to 13 ft. From 13 ft. to 55 ft. From 13 ft. to 55 ft. From 13 ft. to 55 ft.  
 What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage  
 Direction from well? East How many feet? 50

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top Soil			
2	6	Clay Brn			
6	7	Shale Blue			
7	10	Shale & lime lite Gray			
10	41	Red Rock			
41	43	Gravel			
43	46	LIME TAN			
46	48	Gray Shale			
48	53.5	LIME TAN			
53.5	55	Shale Blue			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) Feb 25 87 and this record is true to the best of my knowledge and belief. Kansas  
 Water Well Contractor's License No. 218 This Water Well Record was completed on (mo/day/yr) Feb 28 87  
 under the business name of Zinn Water Well Drilling by (signature) Joseph A. Zinn  
 INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.