


1 LOCATION OF WATER WELL: County: CHASE Fraction: SE 1/4 NE 1/4 NE 1/4 Section Number: 4 Township Number: T 18 S Range Number: R 9 E/W

Distance and direction from nearest town or city street address of well if located within city?  
EMPORIA KS - PRAIRIE ST + HWY 9 W 6 N 2 W 2 N 1/4 W LOT 11

2 WATER WELL OWNER: KEITH HYNSON  
 RR#, St. Address, Box #: RT 1 BOX 8  
 City, State, ZIP Code: STRONG CITY KS 66869  
 Board of Agriculture, Division of Water Resources  
 Application Number: —

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 36 ft. ELEVATION: —  
 Depth(s) Groundwater Encountered: 1. UNKNOWN ft. 2. — ft. 3. — ft.  
 WELL'S STATIC WATER LEVEL: 12 ft. below land surface measured on mo/day/yr 05-28-88  
 Pump test data: Well water was — ft. after — hours pumping — gpm  
 Est. Yield: 125 gpm Well water was — ft. after — hours pumping — gpm  
 Bore Hole Diameter: 8 in. to 36 ft. and — in. to — ft.  
 WELL WATER TO BE USED AS:  
 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well  
 Was a chemical/bacteriological sample submitted to Department? Yes — No X; If yes, mo/day/yr sample was submitted —  
 Water Well Disinfected? Yes X No —

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped —  
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded —  
 7 Fiberglass Threaded —  
 Blank casing diameter: 5 in. to 36 ft. Dia. — in. to — ft. Dia. — in. to — ft.  
 Casing height above land surface: 26 in., weight SCH 40 lbs./ft. Wall thickness or gauge No. SCH 40  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) —  
 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify) —  
 SCREEN-PERFORATED INTERVALS: From 2.6 ft. to 36 ft. From — ft. to — ft.  
 From — ft. to — ft. From — ft. to — ft.  
 GRAVEL PACK INTERVALS: From 20 ft. to 36 ft. From — ft. to — ft.  
 From — ft. to — ft. From — ft. to — ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other —  
 Grout intervals: From 6" ft. to 20 ft. From — ft. to — ft. From — ft. to — ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank HOLDING Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage  
 Direction from well? S How many feet? 50'

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	4"	TOP SOIL			
4"	6'	LIME			
6'	36'	NOT DETERMINED -			
		GAU. CASING REMOVED			
		16' of FILL IN REMOVED			
		TWO VERY OLD RECORDS			
		SHOW DEPTH - 36' + 37' - 8" HOLE			
		COST 81.70 - NOTHING ELSE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 05-30-88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 479 This Water Well Record was completed on (mo/day/yr) 05-30-88 under the business name of EBBERTS DRILLING by (signature) Gregor Ebbert

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T R E/W SEC. 1/4 1/4 1/4