


MW-6

1 LOCATION OF WATER WELL: Fraction SE 1/4 NE 1/4 NW 1/4 Section Number 15 Township Number T 16 S Range Number R 11 E/W
 County: CVEN

Distance and direction from nearest town or city street address of well if located within city?
104 W. 4th AVE., EMPORIA, KANSAS

2 WATER WELL OWNER: LARRY SCOTT
 RR#, St. Address, Box #: BOX 226, 1013 N. 4th, BURLINGTON, Ks. 66734 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Box 226, 1013 N. 4th, Burlington, Ks. 66734 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL 26 ft. ELEVATION: 1140
 Depth(s) Groundwater Encountered 1 34 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield N/A gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 9 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 2 3/8 in. to 21 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface FLUSH MOUNT in., weight lbs./ft. Wall thickness or gauge No. 5CH 40
 TYPE OF SCREEN OR PERFORATION MATERIAL: PVC 10 Asbestos-Cement
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify)
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 36 ft. to 21 ft., From ft. to ft.
 From 36 ft. to 16 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 36 ft. to 16 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout Bentonite 4 Other
 Grout intervals: From 0 ft. to 2 ft., From 2 ft. to 16 ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon Fuel storage (FURNACE) 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? EAST How many feet? 135

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	DK BN CLAY, HARD, DRY			
3	2	BN CLAY, IRON OXIDES, HARD, DRY			
3	26	PALE BK BN CLAY, CALICHE, V. HARD - V FIRM, DRY-MOIST			
26	35	(1) OLIVEY - PALE BN CLAY, CALICHE, NODULES, MOTTLES, V FIRM, MOIST, WET @ 34'			
35	36	BN GRAVELLY CLAY - CLAYEY GRAVEL, 1/2 FRAS, CHERT GRAVEL, SOFT, WET			
FLUSH MOUNT WELL COMPLETION APPROVED BY D. TAYLOR, KASHE-BOW					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/15/03 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. WAC This Water Well Record was completed on (mo/day/yr) 7/15/03 under the business name of QUAD STATE SERVICES, INC. by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.