

LOCATION OF WATER WELL: Fraction NW 1/4 NE 1/4 NW 1/4 Section Number 13 Township Number T 19 S Range Number R 11 E
 County: Lyon
 Distance and direction from nearest town or city street address of well if located within city?

WATER WELL OWNER: Leroy White
 RR#, St. Address, Box #: 1601 E 6th
 City, State, ZIP Code: Emporia KS. 66801
 Board of Agriculture, Division of Water Resources
 Application Number: NA

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

IX	I
NW	NE
SW	SE

DEPTH OF COMPLETED WELL: 52 ft. ELEVATION: 20-24 ft.
 Depth(s) Groundwater Encountered 1. 2' ft. 2. 20-24 ft. 3. 3-20-85 ft.
 WELL'S STATIC WATER LEVEL 2' ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 1-2 gpm. Well water was 10 ft. after 8" hours pumping 952 gpm
 Est. Yield 1-2 gpm. Well water was 10 ft. after 8" hours pumping 952 gpm
 Bore Hole Diameter 10 in. to 10 in. and 8" in. to 952 ft.
 WELL WATER TO BE USED AS:
☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
☐ 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

TYPE OF BLANK CASING USED:
☒ 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)
☒ 2 PVC 4 ABS 7 Fiberglass
 Blank casing diameter 6 in. to 15 ft., Dia 15 in. to 15 ft., Dia 15 in. to 15 ft., Dia 15 in. to 15 ft.
 Casing height above land surface 28 in., weight 160 lbs./ft. Wall thickness or gauge No. 160
 TYPE OF SCREEN OR PERFORATION MATERIAL:
☒ 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
☐ 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
☐ 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
☐ 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 202 11 None (open hole)
☐ 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
☐ 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 16 ft. to 44 ft., From 16 ft. to 44 ft., From 16 ft. to 44 ft., From 16 ft. to 44 ft.
 GRAVEL PACK INTERVALS: From 15 ft. to 52 ft., From 15 ft. to 52 ft., From 15 ft. to 52 ft., From 15 ft. to 52 ft.

GROUT MATERIAL: ☒ 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 2 ft. to 15 ft., From 2 ft. to 15 ft., From 2 ft. to 15 ft., From 2 ft. to 15 ft.
 What is the nearest source of possible contamination:
☐ 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
☐ 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
☐ 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
☐ 13 Insecticide storage Road Ditch
 Direction from well? North How many feet? 25'

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	4	TS BIK			
4	10	CL Red Brown.			
10	14	CL W Gravel			
14	20	Sh yellow Dense			
20	24	LS Dense			
24	26	Sh + Sand Brown yellow			
26	30	LS Dense			
30	38	LS Med			
38	40	Sh LT Gray.			
40	45	LS Dense			
45	52.5	Lime + Sh Green.			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-20-85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 203 This Water Well Record was completed on (mo/day/yr) 6-10-85 under the business name of McNee Drilling & Metals by (signature) J. G. Man
 INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send to three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.