WATER WELL RECORD Form WWC-5 Division of Water Resources; App. No.								
1 LOCA	TION OF	WATER WELL:	Fraction		Section N	umber	Township Number	Range Number
County	1 11	Lyon	NE 4 NW 4	SE ¼	15	.i4: i	T 19 S	R   11   E
County: Lyon NE ½ NW ½ SE ½ 15 T 19 S R 11 E  Distance and direction from nearest town or city street address of well if located within city? 9 Mechanic St, Emporia, KS  Latitude: N ° 2618.30								
Longitude: W ° 2421.08								
2 WAT	OWNER: Richar	d Cipra	I	Elevation: RIM: 1135.25; TOC: 1134.89				
RR#, St. Address, Box # : 23 Locust Lane					Datum: above mean sea level			
City, State, ZIP Code : Emporia, KS, 66801 Data Collection Method: legal survey								
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 33.5 Ft.  LOCATON MW7								
1		N Donth(s) Groun	durator Engagnitered 1		1 <b>V1 VV</b> /	<del>6</del> 2	A 3	£.
ļ.	I AN "X" I ION BOX:	WELL'S STAT	ndwater Encountered I FIC WATER LEVEL	25 41 ft	helow la	nd surfa	nce measured on mol	day/yr 4/0/00
SECI	N BUA:	WELL SSIA	test data: Well water i	43.41 II.	fi	after	hours numn	ing 4/9/09
and the same of th								
W I Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 0 Monitoring well								
-sw-se-								
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs								
S Sample was submitted Water Well Disinfected? Yes No X								
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped								
1 54	or CASII	2 PMP (SP) 6	Asbestos-Cement 9	Other (c	e ille necify he	low)	Maldi	d Clamped
2 DX	IC	A ARS 7	Fiberglass	Outer (s	pecity be	now)	Threa	ded <b>V</b>
PVC 4 ABS 7 Fiberglass Threaded X Blank casing diameter 2 in. to 18.5 ft., Dia in. to ft., Dia in. to ft.  Casing height below land surface 0.36 ft., Weight lbs./ft. Wall thickness or gauge No.								
Casing height below land surface 0.36 ft Weight lbs /ft Wall thickness or gauge No.								
TVPE OF SCREEN OR PERFORATION MATERIAL.								
1 Steel 3 Stainless steel 5 Fiberglass (7) PVC 9 ABS 11 Other (specify)								
TYPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass (7) PVC 9 ABS 11 Other (specify)  2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)								
1 Continuous slot 3 Mill slot 5 Gauze wrapped 2 Torch cut 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)  SCREEN-PERFORATED INTERVALS: From 18.5 ft. to 33.5 ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 16.5 ft. to 33.5 ft. From ft. to ft.								
SCREEN-PERFORATED INTERVALS: From 18.5 ft to 33.5 ft From ft to ft								
Jona Liv	1214 014	.,	From	ft. to		ft. Fr	om ft. f	to ft.
GRAVEL PACK INTERVALS: From 16.5 ft. to 33.5 ft. From ft. to								to ft.
			From	ft. to		ft. Fre	om ft. 1	to ft.
6 CDOUT MATERIAL. 1 Next coment 2 Coment group (2 Posterite (4) Other Coments 0.2.5								
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete: 0-2 ft.  Grout Intervals From 2 ft. to 16.5 ft. From ft. to ft. From ft. to ft.								
What is th	ne nearest so	wirce of possible cor	itamination:	It.		, <sup>1</sup> L.	110111	
What is the nearest source of possible contamination:  1 Septic tank  4 Lateral lines 7 Pit privy  10 Livestock pens 13 Insecticide Storage  16 Other (specify								
2 Sewer lines 5 Cess pool 8 Sewage lagoon (1) Fuel storage 14 Abandoned water well below)								
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well								
Direction	from well?	NW	H	low many	feet? ~9	5		
FROM	TO	LITHO	LOGIC LOG	FROM	TO	T	PLUGGING INT	ERVALS
0	4		k brown silty clay,	15	24	Grav b	prown clay, little silt	
		moderate plasticit					ity, moist	7
4	5		vith silt, Iron Staining	24	25		ed light brown clay,	
	10	veining moderate			20		moderate plasticity	
5	10		little silt, mottled gray	25	30		d light brown clay,	little silt, wet, low
10	15	low to moderate pl	ittle silt, trace gray	30	35		lerate plasticity light brown clay, li	ttle cilt wet low
10	13	mottling, low to m		30	33		lerate plasticity, wit	
		moist	<u> </u>				ub rounded	<u>,</u>
Flushmount waiver from BOW								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged								
under my jurisdiction and was completed on (mo/day/year)  4/9/09  and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 757 Under the business name of Larsen & Associates, Inc.  This Water Well Record was completed on (mo/day/year) 6/22/09  by (signature)								
and the business hanc of Larsen & Associates, Inc.								
INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for								
your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell.								