WATER	R WELL	RECORD Form WWC-5 Division of Water Resources: App. No.
1 LOCA	TION OF	WATER WELL: Fraction Section Number Township Number Range Number Lyon NW NW SE 15 T 19 S R 11 F
Distance a	nd direction	n from nearest town or city street address of well if Global Positioning System (decimal degrees, min. of 4 digits
		1 0 1 1 1 T 1 1 1 1 1 1 1 1 1 1 1 1 1 1
		Latitude: N 38.39/90° Longitude: W 96.17993°
2 WATE	R WELL	OWNER: Richard Cipra Elevation: RIM: 1133.36: TOC: 1133.14
RR#. S	t. Address.	Box # : 23 Locust Lane Datum: above mean sea level
City. S	tate. ZIP C	Box # : 23 Locust Lane   Datum: above mean sea level
3 LOCA	TE WELL	2'S 4 DEPTH OF COMPLETED WELL 32.5 ft. MW11
LOCA		IVI W I I
	AN "X" I	***************************************
SECT	ION BOX:	WELL SSIATIC WATER LEVEL 22.29 II. below land surface measured on morday/yi 11/16/09
	N	Pump test data: Well water was ft. after hours pumping gpn Est. Yield gpm: Well water was ft. after hours pumping gpn
		Est. Yield gpm; well water was it. after nours pumping gpm
- N/W	NE -	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
w	X	1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below
	F !	2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (10) Monitoring well
sw	SE -	
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs
	S	Sample was submitted Water Well Disinfected? Yes No X
5 TYPE	OF CASI	NG USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped
1 Ste	el	RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
(2) PV	C ·	4 ABS 7 Fiberglass Threaded X
Blank casi	ng diamete	r 2 in. to 17.5 ft., Dia in. to ft., Dia in. to f
Casing hei	ght below la	A ABS 7 Fiberglass Threaded X  Threaded X  To in. to 17.5 ft., Dia in. to ft., Dia in. to ft.  Threaded X
TYPE OF	SCREEN (	OR PERFORATION MATERIAL:
1 Ste	el 3 Stair	nless steel 5 Fiberglass (7) PVC 9 ABS 11 Other (specify)
TYPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass (7) PVC 9 ABS 11 Other (specify)  2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)		
ISCREEN	()K PEKE(	DRATION OPENINGS ARE:
1 Co	ntinuous sie	ot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) ter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)
2 LO	DEDEOD A	TED INTERVALS: From 175 ft to 325 ft From ft to ft
SCREEN-	FERFORA	TED INTERVALS:         From         17.5         ft. to         32.5         ft. From         ft. to         ft. to         ft. ft. to         ft. ft. from         ft. to         ft. ft. from         ft. to         ft. ft. from         ft. ft. ft. ft.         ft. ft. ft.         ft. ft. ft.         ft. ft. ft.         ft. ft. ft.         ft. ft. ft.         ft. ft. ft.         ft. ft. ft.         ft. ft. ft.         ft. ft. ft.         ft. ft. ft.         ft. ft. ft.         ft. ft. ft.         ft. ft. ft.         ft. ft. ft.         ft. ft.         ft. ft. ft.         ft. ft. ft.         ft. ft. ft.         ft. ft. ft.         ft. ft. ft.         ft.         ft.
CP.	AMEL DAG	FIGHT II. W II. From II. W II. TO II. W II
UK.	AVELTA	CK INTERVALS: From 15.5 ft. to 32.5 ft. From ft. to ft.
		From ft. to ft. From ft. to f
6 GROU	T MATEI	RIAL: 1 Neat cement 2 Cement grout (3) Bentonite (4) Other Concrete: 0-2 ft. om 2 ft. to 15.5 ft. From ft. to ft. From ft. to ft.
Grout Inte	rvals Fi	om 2 ft. to 15.5 ft. From ft. to ft. From ft. to ft.
What is th	e nearest so	urce of possible contamination:
	ic tank	4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specific
1	er lines	5 Cess pool 8 Sewage lagoon (11) Fuel storage 14 Abandoned water well below)
		er lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well
Direction	from well?	NW How many feet? 350 ft
FROM	TO	LITHOLOGIC LOG FROM TO PLUGGING INTERVALS
0	0.5	Grass, topsoil
0.5	4	Brown silty clay, low plasticity
4	9	Lt brown mottled lt. gray clay with silt, black staining
9	24	Lt brown to lt. gray clay with silt, iron nodules, low
		plasticity
24	30	Lt. brown clay with silt, iron nodules, low plasticity
30	35	Light brown, clay with silt, gravel and coarse angular sand, iron nodules, low plasticity, wet
		Flushmount waiver from BOW
		Transmount warret nom bott
7 CONT	RACTOR'	S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged
		nd was completed on (mo/day/year) 11/17/09 and this record is true to the best of my knowledge and belie
Kansas Water Well Contractor's License No. 757 This Water Well Record was completed of (po/day/year) 12/10/09		
under the business name of Larsen & Associates, Inc. by (signature)		
INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send top three copies to Kansas Department of Health and Environment. Bureau of Water,		
vour records	tion, 1000 SW . Fee of \$5 00	Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for each constructed well. Visit us at http://www.kdheks.gov/waterwell.
		The state of the s