				Form WWC-5			Division of Water Resources; App. No.				
1 LOCA	TION OF	WATER WELL:	Fraction	NTSV	SE				Range Number		
County:	nd direction	Lyon	or city stre	NW ¼	SE %	obal Posit	ioning	T 19 S	R 11 E		
Distance and direction from nearest town or city street address of well if located within city? 8 S Commercial, Emporia, KS Commercial Comme											
Longitude: W 96.17967°											
2 WATER WELL OWNER: Richard Cipra							Elevation: RIM: 1136.80; TOC: 1136.47				
RR#, S	St. Address,	Box # : 23 Loc	ust Lane		I	Datum:	above	e mean sea level			
RR#, St. Address, Box # : 23 Locust Lane City, State, ZIP Code : Emporia, KS, 66801 Data Collection Method: legal survey											
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 33 ft.											
LOCA		Daniel (a) Communication	J4 17		I.	MW12R	A 2	Δ ,	,		
	I AN "X" I	N Depth(s) Groun	idwater En	countered		1 - 1 1	π. 2	π. :	8 ft. /day/yr 6/3/10		
SECT	ION BOX:	WELL S SIA	IIC WAIE	K LEVEL	25.// II.	below land	a suria	ce measured on mo	day/yr 6/3/10		
N Pump test data: Well water was ft. after hours pumping gpm											
Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well											
W E 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (10) Monitoring well											
! ! !	, ,	2 Illigation 4	muusu iai	Domestic	(lawii & go	arden) u	JIVIOIII	itoring wen			
SK SE Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs											
Sample was submitted Water Well Disinfected? Yes No X											
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped											
5 TYPE	OF CASE	NG USED: 5	Wrought I	ron 8	Concrete	e tile	CASI	ING JOINTS: Glue	d Clamped		
1 Ste	eel	3 RMP (SR) 6	Asbestos-	Cement	Other (s	pecity belo	ow)	Weld	led		
PVC4 ABS7 FiberglassThreadedXBlank casing diameter2 in. to18 ft., Diain. toft., Diain. toft.											
Blank casing diameter 2 in. to 18 ft., Dia in. to ft., Dia in. to ft.											
Casing height below land surface 0.33 ft., Weight lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL:											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1 Steel 3 Stainless steel 5 Fiberglass (7) PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
1 Continuous slot @Mill slot 5 Gauge arranged 7 Torch out 9 Drilled holes 11 None (open hole)											
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 18 ft. to 33 ft. From ft. to ft.											
SCREEN	-PEKFOKA	TED INTERVALS	From	18	n. to	33	n. Fro	omtt.	tott.		
From ft. to ft. From ft. to ft.											
GRAVEL PACK INTERVALS: From 16 ft. to 33 ft. From ft. to ft.											
From ft. to ft. From ft. to ft.											
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout (3 Bentonite (4) Other Concrete: 0-1 ft.											
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete: 0-1 ft. Grout Intervals From 1 ft. to 16 ft. From ft. to ft. From ft. to ft.											
What is the nearest source of possible contamination:											
	tic tank	4 Lateral li			0 Livestoo			cticide Storage	16 Other (specify		
2 Sewer lines 5 Cess pool 8 Sewage lagoon (1) Fuel storage 14 Abandoned water well below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well											
Direction	from well?	N	on 9 reec	iyard i		feet? ~22		weil gas weil			
		N					5 IL				
FROM	TO	LITHO	LOGIC LO)G	FROM	ТО		PLUGGING IN	TERVALS		
0	0.5	Concrete									
0.5	5	Brown stiff silty clay							· · · · · · · · · · · · · · · · · · ·		
10	10 15	Brown with gray mottl Gray, stiff silty clay	ing, stiff silty	clay	 -						
15	19	Brown with gray mottl	ing, stiff silts	clav							
19	20	Gray, stiff silty clay	ing, star sart	ciny		-	77.00	74.6			
20	25	Gray with mottling, sti	ff silty clay						14		
25	33	Gray with mottling, sti		ith sand and							
		gravel				I	Flushmo	unt waiver from BOW			
7 CONTE	DACTORS	CODIANDONA	EDIC OFF	TIBLOATEO	NI. TT		6	1 1 (2)	1 (0)		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/3/10 and this record is true to the best of my knowledge and belief.											
Kansas Wa	ter Well Con	ntractor's License No.	757	This Wat		cord was co	nipleted	on (medday/year)	6/24/10		
		of Larsen & Asse			by (signatu		1		VIZTI IV		
I							artment	K Health and Environme	ent, Bureau of Water		
INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell.											
your records	. rec 01 33.00	Tor each constructed we	i. visit us at	лир.//www.kdne	rs.guv/water	WCII.		- / /			