LOCATION OF MATERIALE.	and the state of 		212 ID No.	Range Number
LOCATION OF WATER WELL: ounty: Lyons	Fraction SE 1/4 SE 1/4 SW	Section Number	Township Number	R 11 E
istance and direction from nearest town	or city street address of well if located with		<u> </u>	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
05 S. Commercial St. – Empor				
WATER WELL OWNER: Pravink				
R#, St. Address, Box # : 505 S. 0	Commercial St.		Board of Agriculture, Div	ision of Water Resources
city, State, ZIP Code : Empori	ia, KS 66801		Application Number:	
LOCATE WELL'S LOCATON WITH	4 DEPTH OF COMPLETED WELL	30.5 # FLEV	ATION: 1121	1.80 (TOC)
AN A INSCENSION BOX.	Denth(s) Groundwater Encountered 1	ff	2 ff	3 ft.
	Depth(s) Groundwater Encountered 1 WELL'S STATIC WATER LEVEL 19.	79 ft helow TOC r	neasured on mo/day/yr	09/24/13
NWNE	Pump test data: Well water wa	as f	after hours	oumpina apm
w E	Est. Yield gpm: Well water wa	as f	after hours	oumpina apm
	Bore Hole Diameter 8.25 in to	30.5	ft and	n. to ft.
SW SE	Bore Hole Diameter 8.25 in. to WELL WATER TO BE USED AS: 5 Publ 1 Domestic 3 Feed lot 6 Oil fil	ic water supply	8 Air conditioning 1	1 Injection well
x	1 Domestic 3 Feed lot 6 Oil fi	eld water supply	9 Dewatering 1	2 Other (Specify below)
	2 Irrigation 4 Industrial 7 Law			1
9	Was a chemical/bacteriological sample sub	· · · · · · · · · · · · · · · · · · ·		
	submitted	Wa	ter Well Disinfected? Yes	No X
TYPE OF BLANK CASING USED:	5 Wrought Iron	8 Concrete tile	CASING JOINTS: Glue	
1 Steel 3 RMP (S	SR) 6 Asbestos-Cement	9 Other (specify belo	w) Wel	ded
2 PVC 4 ABS	7 Fiberglass			_{ided} Flush
Blank casing diameter 2	in. to 15.5 ft., Dia 3.72 in., weight 0. 7	in. to	ft., Dia	in. to ft.
Casing height below land surface	3.72 in., weight 0.7	703 lbs./ft.	Wall thickness or gauge No	SCH. 40
YPE OF SCREEN OR PERFORATION		7 PVC	10 Asbestos-cem	ent
1 Steel 3 Stainle	ess steel 5 Fiberglass	8 RMP (SR)	11 Other (specify))
	ess steel 5 Fiberglass nized steel 6 Concrete tile GS ARE: 5 Gauzed	9 ABS	12 None used (or	
CREEN OR PERFORATION OPENING				11 None (open noie)
The state of the s	Mill slot 6 Wire wra		9 Drilled holes	
2 Louvered shutter 4			10 Other (specify)	 4x
SCREEN-PERFORATED INTERVALS:				
ODANEL BACK INTERVALO.	From ft. to From 12.5 ft. to	305 # 1	rom ff	to ft.
GRAVEL PACK INTERVALS:	From 12.9 1. to	4 I	rom ft.	to ft.
a analytical	From ft. to	2 Danianita	rom π.	
GROUT MATERIAL: 1 Neat c	ement 2 Cement grout	3 Demonite	4 Other	eran eran eran eran eran eran eran eran
	π. το 12.3 π. From	π. το	L FIOIII	bandoned water well
What is the nearest source of possible of 1 Septic tank	4 Lateral lines 7 Pit privy	10 Lives	storage 15 O	
2 Sewer lines	5 Cess pool 8 Sewage la	- 1, 1, 1 - 1 - 1, 1, 1 - 1 - 1, 1, 1 - 1 -		ther (specify below)
3 Watertight sewer lines	6 Seepage pit 9 Feedyard	· · · · · · · · · · · · · · · · · · ·	ticide storage	THE STATE OF THE S
Direction from well? South	a sample of the		feet? 55	
FROM TO CODE	LITHOLOGIC LOG	FROM TO	PLUGGING	INTERVALS
	psoil / Silty Fill			<u> </u>
	t with Clay	<u> </u>		
	ty Clay	<u> </u>	<u> </u>	
15 18 Sil 18 20 Cla	ity Clay / Clay av		<u> </u>	
	ay It with Clay	<u> </u>	<u> Carrier and Arthur a</u>	
25 29 Sil				
	avel, coarse grained			
	nale		- Charles and the second se	
			one.	. Canada ya maraki da mayaraki a mayaraki da
			GPS:	290
			Latitude: N 38.3917	
29.5 30.5 Sh	D'S CEDTIFICATION: This water well was	(1) constructed (2) ===	Longitude: W 96.18	0667
7 CONTRACTOR'S OR LANDOWNER	R'S CERTIFICATION: This water well was	· · · · · · · · · · · · · · · · · · ·	Longitude: W 96.18 onstructed, or (3) plugged un	10667 der my jurisdiction and was
7 CONTRACTOR'S OR LANDOWNED Completed on (mo/day/yr)	09/18/13	and this record is	Longitude: W 96.18 onstructed, or (3) plugged untitue to the best of my knowle	10667 der my jurisdiction and was edge and belief. Kansas
7 CONTRACTOR'S OR LANDOWNER	09/18/13	and this record is	Longitude: W 96.18 onstructed, or (3) plugged un	10667 der my jurisdiction and was edge and belief. Kansas