WATE	R WELL	RECORD Form WWC-5	Di	Division of Water Resources; App. No.														
1 LOCA	TION OF	WATER WELL: Fraction	,	Section Nu	mber	Township Num	ber	Range Number										
County:	and direction	Marion SE ½ NE ½ SW on from nearest town or city street address of we	11 if	Global Posi	tioning	System (decima	S dear	R 2 E										
located within city? 500 East Grand, Hillsboro, KS Latitude: N 38.35268°																		
			Longitude: W 97.19837°															
2 WAT	OWNER: USD 410		Elevation: RIM: 1429.78 TOC: 1429.58 Datum: above mean sea level Data Collection Method: legal survey															
City S	, Box # : 812 East A Street code : Hillsboro, KS 67063		Datum:	ction M	e mean sea ievei	rvev												
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 40 ft.																		
LOCA				MW6														
	I AN "X" I	N Depth(s) Groundwater Encountered 1			ft. 2	fi	ı. 3	ft.										
SECT	ION BOX		70	ft. below lan	id surfa	ce measured on	mo/da	ay/yr 9/25/08										
	N Pump test data: Well water was ft. after hours pumping gp																	
Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well																		
									-sw	SE - Was a shemical/hasterialogical sample submitted to Department? Ves - No. V : If yes ma/day/was								
									Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/y Sample was submitted Water Well Disinfected? Yes No X								No X	
									5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped									
5 TYPE	OF CASI	NG USED: 5 Wrought from 8 (oncr	ete tile	CASI	ng join 12: G	luea	Clamped										
2 PV	1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded																	
PVC 4 ABS 7 Fiberglass Threaded X Blank casing diameter 2 in. to 25 ft., Dia in. to ft., Dia in. to ft. Casing height below land surface 0.20 ft., Weight Ibs./ft. Wall thickness or gauge No.																		
Casing height helpw land surface 0.20 ft Weight lhs /ft Wall thickness or gauge No.																		
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify)																		
1 Steel 3 Stainless steel 5 Fiberglass (7) PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)																		
ISCREEN OR PERFORATION OPENINGS ARE:																		
1 Continuous slot (3) Mill slot 5 Guaze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 25 ft. to 40 ft. From ft. to ft.																		
SCREEN-PERFORATED INTERVALS: From 25 ft. to 40 ft. From ft. to ft.																		
1		From ft.	. to		n. Fro	om	ft. to) ft.										
GR	AVEL PA	CK INTERVALS: From 23 ft.	. to	40	ft. Fro	om	ft. to	ft.										
		CK INTERVALS: From 23 ft. From ft.	to		ft. Fro	om ,	ft. to)ft. _.										
6 GROUT MATERIAL: 1 Neat cement (2) Cement grout (3) Bentonite (4) Other Concrete: 0-2'																		
6 GROUT MATERIAL: 1 Neat cement (2) Cement grout (3) Bentonite (4) Other Concrete: 0-2' Grout Intervals From 2 ft. to 16 ft. From 16 ft. to 23 ft. From ft. to ft.																		
What is the nearest source of possible contamination:																		
	tic tank			tock pens		ecticide Storage		16 Other (specify										
2 Sewer lines 5 Cess pool 8 Sewage lagoon (1) Fuel storage 14 Abandoned water well below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well																		
	from well?			ny feet? ~95		well/ gas well												
						DLUCCDIC	NITE	DVALC										
FROM	TO 5	LITHOLOGIC LOG Silty clay, dark brown, little coarse sand, moderate	ROM	M TO		PLUGGING	INTE	RVALS										
		plasticity, moist																
5	20	Olive tan clay, mottled yellow brown, with silt,																
		low to moderate plasticity, moist																
20	25	Clay, yellow brown, with silt, some olive gray																
25	40	mottling, CaCO ₃ crystallization, moist																
25	40	Clay, yellow olive brown, some silt, little limestone																
		giaron, moist			Flushn	nount waiver fr	om B	ow										
					_													
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/23/08 and this record is true to the best of my knowledge and belief.																		
		nd was completed on (mo/day/year) 9/23/0																
				ature)	nipietec	i on (mo/day/year)		140/00										
Į.				·	artment	of Health and Enviro	nment	Rureau of Weter										
INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522 Send one to WATER WELL OWNER and retain one for																		
your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell.																		