## CORRECTED

WATER WELL R	ECORD	Form WV	VC-5	Divi	ision of Water	r Resources App. No	o. L	
1 LOCATION OF WATER WELL:		Fraction 5W 1/4 SW 1/4 NW	1/4 SW 1/4	Section		Township No. T 19 S		
Street/Rural Address of Well Location; if unknown, distance & direction			Global Positioning System (GPS) information:					
from nearest town or intersection: If at owner's address, check here .					Latitude: .38.35192(in decimal degrees)			
131 SOUTH MAIN, HILLSBORO, KS				Longitude: 97.20563 (in decimal degrees)				
101 000 111 MI ditt, MEEODONO, NO				Elevation: .1430.60				
2 MATERIAL ONATER				Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27				
2 WATER WELL OWNER: KDHE				Collection Method:				
RR#, Street Address, Box #: 1000 SW JACKSON STREET				GPS unit (Make/Model:)				
City, State, ZIP Code : TOPEKA, KS 66612-1367			Digital Map/Photo, Topographic Map, Land Survey					
Est. Accuracy: □ <3 m, □ 3-5 m, □ 5-15 m, □ >15 m   3 LOCATE WELL								
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 32								
SECTION BOX:	SECTION BOX: Depth(s) Groundwater Encountered (1),~26,							
N	N WELL'S STATIC WATER LEVEL. 25.98ft. below land surface measured on mo/day/yr							
Pump test data: Well water wasft. after hours pumping gpm								
EST. YIELDgpm. Well water wasft. after hours pumpinggpm								
W         E   Bore Hole Diameterin. toft., andin. toft.								
X <sub>SW</sub> Domestic Feedlot Oil field water supply Dewatering Other (Specify below)								
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No								
S If yes, mo/day/yr sample was submitted								
l mile  Water well disinfected? ☐ Yes ☑ No								
5 TYPE OF CASING USED: Steel V PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter .2								
Casing height above land surface4.99								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel ☐ Other (Specify)								
Brass Galvanized Steel None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous slot       ☑ Mill slot       ☐ Gauze wrapped       ☐ Torch cut       ☐ Drilled holes       ☐ None (open hole)         ☐ Louvered shutter       ☐ Key punched       ☐ Wire wrapped       ☐ Saw cut       ☐ Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
From								
GRAVEL PACK INTERVALS: From								
From								
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ✓ Bentonite ☐ Other								
Grout Intervals: From .1								
What is the nearest source of possible contamination:								
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage 🗹 Other (specify below)								
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well								
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well ☐ Lust Site ☐ Direction from well ☐ Distance from well Distance from well Distance from well Distance from well Distance from w								
·····	LITHOLO	OIC LOG	FROM	TO	LITHO, L	OG (cont.) or PLU	UGGING INTERVALS	
	P SOIL							
	AY, SILTY							
	AY, SILTY							
	AY, SILTY ALE					14140		
25 32 SH.	ALC			-		MW10		
<u> </u>						V. 41-7		
7 CONTRACTORS	ODIANDONST	Dic CERTIFICATIO	No This			4.1 🗇 :		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☑ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) .05/17/2011 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 594 This Water Well Record was completed on (molday/figer) 960/172011								
under the business name ofCoranco Great Plains, Inc								
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephone 785-296-5522.	Send one copy to WA	TER WELL OWNER and	etain one for	your recor	ds. Include fe	ee of \$5.00 for each	constructed well. Visit us at	
http://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy								