



Corrected

MW-702C

WATER WELL RECORD Form WWC-5 1263655

Division of Water Resources App. No.

Blank box for Division of Water Resources App. No.

Well ID

BJP-16

[X] Original Record [] Correction [] Change in Well Use

1 LOCATION OF WATER WELL: County: Linn Fraction NW 1/4 SE 1/4 NE 1/4 NE 1/4 Section Number 27 Township Number T 19 S Range Number R 25 [X] E [] W

2 WELL OWNER: Last Name: Business: KCP&L Address: 25166 E 2200th Road City: La Cygne State: KS ZIP: 66040 Street or Rural Address where well is located: If at owner's address, check here: [X]

3 LOCATE WELL WITH 'X' IN SECTION BOX: N W E S 1 mile. 4 DEPTH OF COMPLETED WELL: 55 ft. 5 Latitude: 38.37185 Longitude: 94.62456 Datum: [] WGS 84 [X] NAD 83 [] NAD 27 Elevation: 882 880.5 ft. [X] Ground Level [] TOC

7 WELL WATER TO BE USED AS: 1. Domestic: [] Household [] Lawn & Garden [] Livestock [] Irrigation [] Feedlot [] Industrial 2. [] Public Water Supply: well ID 3. [] Dewatering: how many wells? 4. [] Aquifer Recharge: well ID 5. [] Monitoring: well ID 6. [] Environmental Remediation: well ID 7. [] Air Sparge [] Soil Vapor Extraction [] Recovery [] Injection 8. [] Oil Field Water Supply: lease 9. Test Hole: well ID 10. [] Cased [] Uncased [] Geotechnical 11. Geothermal: how many bores? 12. a) Closed Loop [] Horizontal [] Vertical b) Open Loop [] Surface Discharge [] Inj. of Water 13. [] Other (specify):

Was a chemical/bacteriological sample submitted to KDHE? [] Yes [X] No If yes, date sample was submitted: Water well disinfected? [] Yes [X] No

8 TYPE OF CASING USED: [] Steel [X] PVC [] Other CASING JOINTS: [] Glued [] Clamped [] Welded [X] Threaded Casing diameter: 2 in. to 55 ft. Diameter: 36 in. to 154 inch Casing height above land surface: 36 in. Weight: lbs./ft. Wall thickness or gauge No. 0.154 inch TYPE OF SCREEN OR PERFORATION MATERIAL: [] Steel [] Stainless Steel [] Fiberglass [X] PVC [] Brass [] Galvanized Steel [] Concrete tile [] None used (open hole) [] Other (Specify) SCREEN OR PERFORATION OPENINGS ARE: [] Continuous Slot [X] Mill Slot [] Gauze Wrapped [] Torch Cut [] Drilled Holes [] Other (Specify) [] Louvered Shutter [] Key Punched [] Wire Wrapped [] Saw Cut [] None (Open Hole) SCREEN-PERFORATED INTERVALS: From 50 ft. to 55 ft. From 55 ft. to 48 ft. GRAVEL PACK INTERVALS: From 48 ft. to 55 ft. From 55 ft. to 48 ft.

9 GROUT MATERIAL: [] Neat cement [] Cement grout [X] Bentonite [X] Other cement-bentonite Grout Intervals: From 1 ft. to 44.5 ft. From 44.5 ft. to 48 ft. From 48 ft. to 48 ft. Nearest source of possible contamination: [] Septic Tank [] Lateral Lines [] Pit Privy [] Livestock Pens [] Insecticide Storage [] Sewer Lines [] Cess Pool [] Sewage Lagoon [] Fuel Storage [] Abandoned Water Well [] Watertight Sewer Lines [] Seepage Pit [] Feedyard [] Fertilizer Storage [] Oil Well/Gas Well [] Other (Specify) Direction from well? Distance from well? ft.

Table with columns: 10 FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Rows: 0 to 13.2 (clay), 13.2 to 13.8 (limestone), 13.8 to 55.56 (shale). Includes Notes section.

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was [X] constructed, [] reconstructed, or [] plugged under my jurisdiction and was completed on (mo-day-year) 08/05/2015 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 529 This Water Well Record was completed on (mo-day-year) 09/08/2015 under the business name of Geotechnology, Inc.