

007227

1) LOCATION OF WATER WELL: County: <u>Marion</u>	Fraction: <u>NW 1/4 NW 1/4 SW 1/4</u>	Section Number: <u>33</u>	Township Number: T <u>19</u> S	Range Number: R <u>3</u> <u>EW</u>
--	---------------------------------------	---------------------------	--------------------------------	------------------------------------

Distance and direction from nearest town or city street address of well if located within city?

1940 Navajo Rd, Canada

2) WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :	<u>Kenneth Sandwell</u> <u>1940 Navajo Rd</u> <u>Canada KS 66261</u>	Board of Agriculture, Division of Water Resources Application Number:
---	--	--

3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4) DEPTH OF COMPLETED WELL: <u>29</u> ft. ELEVATION:
---	--

Depth(s) Groundwater Encountered 1. 15 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter. 8.5 in. to 2.9 ft., and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well M.W.-6

Was a chemical/bacteriological sample submitted to Department? Yes. No. X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X

5) TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued. Clamped.
-------------------------------	----------------	-----------------	--

Blank casing diameter 2 in. to 19 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface. Flush in., weight 203 lbs./ft. Wall thickness or gauge No. Sch. 40

TYPE OF SCREEN OR PERFORATION MATERIAL:	10 Asbestos-cement
---	--------------------

SCREEN OR PERFORATION OPENINGS ARE:	11 Other (specify)
-------------------------------------	--------------------------

SCREEN-PERFORATED INTERVALS:	12 None used (open hole)
------------------------------	--------------------------

6) GROUT MATERIAL:	1 Neat cement	2 Cement grout	<u>3 Bentonite</u>	<u>4 Other</u> <u>concrete</u>
--------------------	---------------	----------------	--------------------	--------------------------------

Grout Intervals: From. 0 ft. to 1 ft., From. 1 ft. to 17 ft., From. ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Clay, dk brown			
3	6.5	Shale, weathered, olive			
6.5	8	Limestone, gray			
8	28	Shale, weathered, olive			
28	29	Limestone			

7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1) constructed</u> , <u>(2) reconstructed</u> , or <u>(3) plugged</u> under my jurisdiction and was completed on (mo/day/year) <u>12/31/01</u> and this record is true to the best of my knowledge and belief, Kansas Water Well Contractor's Licence No. <u>531</u> This Water Well Record was completed on (mo/day/yr) <u>1/18/02</u> under the business name of <u>Geotechnical Services, Inc</u> by (signature) <u>Allen M. ...</u>
