


1 LOCATION OF WATER WELL: Fraction NW 1/4 SW 1/4 1/2 1/4 Section Number 32 Township Number T 19 S Range Number R 4 E
 County: Marion

Distance and direction from nearest town or city street address of well if located within city?
In City Marion 406 N Roosevelt

2 WATER WELL OWNER: Orville Pfeiffer
 RR#, St. Address, Box #: 406 N Roosevelt Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Marion, KS, 66861 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL 83 ft. ELEVATION: ft.
 Depth(s) Groundwater Encountered, 1 75 ft. 2 ft. 3 4-1-03 ft.
 WELL'S STATIC WATER LEVEL 32 ft. below land surface measured on mo/day/yr 4-1-03
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 20 gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
 2 PVC 4 ABS 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 6.5 ft. Dia 12 in. to ft. Dia in. to ft.
 Casing height above land surface in., weight Class 160 lbs./ft. Wall thickness or guage No. 214
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-Cement
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify)
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 65 ft. to 83 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 20 ft. to 83 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 20 ft., From ft. to ft. From ft. to ft.
 What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
 Direction from well? S How many feet? 10

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>4</u>	<u>Clay</u>			
<u>4</u>	<u>20</u>	<u>lime</u>			
<u>20</u>	<u>45</u>	<u>Yellow Shale</u>			
<u>45</u>	<u>52</u>	<u>Blue Clay</u>			
<u>52</u>	<u>68</u>	<u>Red Shale</u>			
<u>68</u>	<u>75</u>	<u>Lime</u>			
<u>75</u>	<u>76</u>	<u>Water</u>			
<u>76</u>	<u>83</u>	<u>Lime & Gray Rock</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-1-03 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 100 This Water Well Record was completed on (mo/day/yr) 4-1-03 under the business name of Bac Khu & Drilling by (signature) [Signature]