

#5

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4

1/4

1/4

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: CHASE		SW 1/4 SE 1/4 NE 1/4	8	T 19 S	R 6 EW
Distance and direction from nearest town or city street address of well if located within city? APPROX 9.5M W. ELMDALE - MIDDLE CREEK RD.					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 55 ft. ELEVATION:			
		Depth(s) Groundwater Encountered UNKNOWN ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 24 ft. below land surface measured on mo/day/yr 08-28-98			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter. in. to ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well LIVESTOCK			
		Was a chemical/bacteriological sample submitted to Department? Yes. No. X If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile 11 Injection well			
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below) 12 Other (Specify below)			
Blank casing diameter 5 in. to 55 ft. Dia. in. to ft. Dia. in. to ft.		7 Fiberglass 10 Asbestos-cement			
Casing height above land surface 22 in., weight SCH 40 lbs./ft. Wall thickness or gauge No.		8 RMP (SR) 11 Other (specify)			
TYPE OF SCREEN OR PERFORATION MATERIAL:		12 None used (open hole)			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		7 PVC 10 Asbestos-cement			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		11 Other (specify)			
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		5 Gauzed wrapped			
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)		11 None (open hole)			
SCREEN-PERFORATED INTERVALS: From 40 ft. to 50 ft. From ft. to ft.		3 Bentonite 4 Other			
GRAVEL PACK INTERVALS: From 20 ft. to 55 ft. From ft. to ft.		6 Cement grout			
From ft. to ft. From ft. to ft.		1 Neat cement			
From ft. to ft. From ft. to ft.		2 Cement grout			
From ft. to ft. From ft. to ft.		3 Bentonite			
From ft. to ft. From ft. to ft.		4 Other			
6 GROUT MATERIAL:		Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft.			
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage NONE IN AREA		3 Watertight sewer lines 6 Seepage pit 9 Feedyard			
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	50	UNKNOWN			10" GALV. CASING - RUSTED
50	55	SHALE			OUT AT S.L. - APPROX 24'
					STILL IN PLACE.
					ORIGINAL BORE
					WAS LARGER THAN 10.5"
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 08-28-98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 479 This Water Well Record was completed on (mo/day/yr) 09-23-98 under the business name of EBBERTS DRILLING by (signature) <i>[Signature]</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					