KOLAR Document ID: 1377274

				Division of Water				
<u> </u>		ge in Well Use		ources App. No		Well ID	N	
1 LOCATION OF WATER WELL: County:		Fraction 1/4 1/4 1/4 1/4		ction Number	Township Numb		Range Number R □ E □ W	
2 WELL OWNER: L			ıral Address v					
2 WELL OWNER: Last Name: First: Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here:								
Address:								
Address:	G	710						
City: 3 LOCATE WELL	State:	ZIP:						
WITH "X" IN	4 DEPTH OF COM	IPLETED WELL: .	f	t. 5 Latitude :(decimal degrees)				
SECTION BOX:		Encountered: 1)			ude:			
N		3) ft., or 4) □			☐ WGS 84 ☐ NA		IAD 27	
		TER LEVEL:, measured on (mo-day-			for Latitude/Longitude S (unit make/model:		,	
NW NE		, measured on (mo-day-			(WAAS enabled?		,	
		vater was ft		☐ Land Survey ☐ Topographic Map				
E E		s pumping		Online Mapper:				
SW SE		vater was ft						
	after hours pumping gpm Estimated Yield:gpm			6 Elevation :ft. ☐ Ground Level ☐ TOC				
S	Bore Hole Diameter: in. to ft. and			Source: Land Survey GPS Topographic Map				
mile		in. to		Other				
7 WELL WATER TO BE USED AS:								
1. Domestic:		ater Supply: well ID			Field Water Supply: 16	ease		
Household		ig: how many wells?		11. Test Hole: well ID				
Lawn & Garden		echarge: well ID		☐ Cased ☐ Uncased ☐ Geotechnical				
☐ Livestock 2. ☐ Irrigation		g: well IDal Remediation: well ID		12. Geothermal: how many bores?				
3. ☐ Feedlot	9. Environmenta			b) Open Loop Surface Discharge Inj. of Water				
4. ☐ Industrial		13. Other (specify):						
4.								
Water well disinfected? \square Yes \square No								
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter in. to ft., Diameter ft., Diameter ft.								
Casing height above land surface in. Weight lbs./ft. Wall thickness or gauge No								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel ☐ Fiberglass ☐ PVC ☐ Other (Specify)								
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:								
Continuous Slot ☐ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)								
□ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole)								
SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft., From ft., From ft. to ft.								
GRAVEL PACK INTERVALS: From ft. to ft., From ft., From ft. to ft.								
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout Intervals: From								
Nearest source of possible contamination:								
☐ Septic Tank ☐ Sewer Lines	☐ Lateral Line ☐ Cess Pool	es ☐ Pit Privy ☐ Sewage Lag] Livestock Pen] Fuel Storage		cide Storage oned Water		
☐ Watertight Sewer Lin				Fertilizer Stora		ell/Gas Well		
Other (Specify)								
Direction from well? Distance from well? .								
10 FROM TO	LITHOLOG	GIC LOG	FROM	TO I	LITHO. LOG (cont.) or	r PLUGGIN	G INTERVALS	
			1					
			Notes:					
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged								
under my jurisdiction at	under my jurisdiction and was completed on (mo-day-year)							
under the business name of								
	Send one copy to WATER W	ELL OWNER and retain of	ne for your re	cords. Fee of \$5.0	00 for each constructed we	ell.		
KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3565.								
Visit us at http://www.kdheks.gov/waterwell/index.html KSA 82a-1212								