


1 LOCATION OF WATER WELL: County: Cherokee Fraction: NW 1/4 SW 1/4 SW 1/4 Section Number: 3 Township Number: T 19 S Range Number: R 9 E

Distance and direction from nearest town or city street address of well if located within city?
7 East 1/2 North Strong City Ks.

2 WATER WELL OWNER: Erkine Lind. Board of Agriculture, Division of Water Resources
 RR#, St. Address, Box #: RA1 Application Number: N/A
 City, State, ZIP Code: Strong City Ks 66869

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 58' ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL: 37 ft. below land surface measured on mo/day/yr 6-18-02
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 10-15 gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 9 5/8 in. to 32 in. and 8 in. to 58 in.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
 2 PVC 4 ABS 7 Fiberglass Threaded
 Blank casing diameter: 6 in. to 38 in. Dia. in. to ft. Dia. in. to ft.
 Casing height above land surface: 18" in., weight: 160 lbs./ft. Wall thickness or gauge No. 160
 TYPE OF SCREEN OR PERFORATION MATERIAL: PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From: 38 ft. to 57 ft. From ft. to ft.
 From ft. to ft. From ft. to ft.
 GRAVEL PACK INTERVALS: From ft. to ft. From ft. to ft.
 From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: Neat cement 2 Cement grout Bentonite 4 Other
 Grout Intervals: From: 4 ft. to 24 ft. Bentonite From: 24 ft. to 32 ft. Neat cement From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? North East How many feet? 150 + Lagoon Lines 60'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	TS Bk.	47	58	LS cherty, variegated
1	4	CL Brown.			
4	6	yellow-green.			Had some silicez sand.
6	9	CL W-Gravel Red.			BUT DON'T KNOW SOURCE
9	12 1/2	Calc SH-Blue			Set shale cut taken 3 1/2'
12 1/2	15	LS Med Dense			2 Sacks Portland 4 to
15	20	Sh Cream.			Pit Less Adapter 14 Bentonite
20	25	LS Cream.			Fill to surface with
25	29	Sh Black. some Red			Chy Soil
	29 1/2	Lost Fluid.			
		Reamed Hole + 9 5/8 set 8"			
		Steel work pipe 32'			
	32	Lime + shale			
	43	Sh Dark			
	43	46			
	46	47			
		Soft Lime			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-18-02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 203 This Water Well Record was completed on (mo/day/yr) 6-26-02 under the business name of MS Nec Drilling & Metals by (signature) [Signature]

OFFICE USE ONLY