City, State, ZIP Code Collow Wath Application Number: Collow Wath Depth of CoMPLETED WELL O. ft. ELEVATION:
Detance and direction from pearest, town or city street address of well if located, withing city? WATER WELL OWNER: So
WATER WELL OWNER: RR#, St. Address, Box #: City, State, ZIP Code : Collow Wood Falls, K'S 64845 Board of Agriculture, Division of Water Re. City, State, ZIP Code : Collow Wood Falls, K'S 64845 Application Number: LOCATE WELL'S LOCATION WITH DEPTH OF COMPLETED WELL 0.9 ft. ELEVATION: Depth(s) Groundwater Encountered 1 9 ft. below land surface measured on morday/yr 3 7 Pump test data: Well water was ft. after hours pumping Est. Yield 7.5 gpm Well water was ft. after hours pumping Est. Yield 7.5 gpm Well water was ft. after hours pumping Est. Yield 7.5 gpm Well water was ft. after hours pumping Est. Yield 7.5 gpm Well water was ft. after hours pumping Est. Yield 7.5 gpm Well water was ft. after hours pumping Est. Yield 7.5 gpm Well water was ft. after hours pumping Est. Yield 7.5 gpm Well water supply 8 Air conditioning 11 injection well Was a chemical/bacterological sample submitted to Department? Yes Was a chemical/bacterological sample submitted to Department? Yes No. X If yes, mordaylyr sample with was a chemical/bacterological sample submitted to Department? Yes Water Well Disinfected? (**e*) No Type OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped Water Well Disinfected? (**e*) No Water Well Disinfected? (**e*) No Welded X Clamped 9 Other (specify below) Welded X Clamped Blank casing diameter 5 in to ft. Dia in to Casing height above land surface 1 1 1 1 1 1 1 1 1 LOCATION DEPENDENT ON MATERIAL: Over 1 1 1 1 1 1 1 1 1
WATER WELL OWNER: RRM*, St. Address, Box #: Collowwood Falls, KS 64845 Board of Agriculture, Division of Water Re Application Number: DOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered
Board of Agriculture, Division of Water Re Application Number: Coll
Collow wood Falls XS 66875 Application Number: Collow wood Falls XS 66875 Application Number: Collow wood Falls XS 66875 Application Number: Collow wood Falls XS 66875 Application Number: Collow wood Falls XS 66875 Application Number: Collow wood Falls XS 66875 Application Number: Collow wood Falls XS 66875 Application Number: Collow wood Falls XS 66875 Application Number: Collow wood Falls XS 68875 Application Number: Collow wood Falls Application
Depth(s) Groundwater Encountered 1. 9. ft. 2. ft. 3. Depth(s) Groundwater Encountered 1. 9. ft. 2. ft. 3. Depth(s) Groundwater Encountered 1. 9. ft. 2. ft. 3. Depth(s) Groundwater Encountered 1. 9. ft. below land surface measured on mordaylyr July 13. 9. Pump test data: Well water was ft. after hours pumping Est. Yield 75 gpm; Well water was ft. after hours pumping hours pumping Est. Yield 75 gpm; Well water was ft. after hours pumping hours pumping 11 injection well 2 largeating 12 Other (Specify below 2 largeating 12 Other (Specify below 2 largeating 13 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below 2 largeating 13 Feedlot 7 Each achemical/bacteriological sample submitted to Department? Yes. No. X. if yes, mor/daylyr sample water Well Disinfected? Sp. No Yes more achemical/bacteriological sample submitted to Department? Yes. No. X. if yes, mor/daylyr sample water Well Disinfected? Sp. No Yes more yes yes yes. Yes more yes yes yes yes yes yes yes yes yes ye
Depth(s) Groundwater Encountered 1. 9. ft. 2 below land surface measured on moidaylyr 3. WELL'S STATIC WATER LEVEL 8. ft. below land surface measured on moidaylyr 3. Pump test data: Well water was ft. after hours pumping sw ft. after hours pumping hours pumping sw ft. after hours pumping hours pumping hours pumping hours pumping sw sw ft. after hours pumping hours pumping sw
Pump test data: Well water was ft. after hours pumping Est. Yield Pump test data: Well water was ft. after hours pumping Sore Hole Diameter 8 9 6 in. to 7 ft. and 2 1 in. to 10 10 0 in. to 10 0 0 in. in. to 10
Est. Yield 75. gpm: Well water was ft. after hours pumping. Bore Hole Diameter 8
Est. Yield 75. gpm: Well water was ft. after hours pumping. Bore Hole Diameter 8
Bore Hole Diameter 876 in. to 7. A. and 6. A. in. to 7. A. and 6. A. in. to 7. A. and 6. A. in. to 7. A. and 8. Air conditioning 11 Injection well 11 Injection well 12 Injection well 13 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below 12 Injection well 14 Injection well 15 Injection well 15 Injection well 15 Injection well 16 Oil field water supply 9 Dewatering 12 Other (Specify below 12 Injection well 15 Injection well 16 Oil field water supply 9 Dewatering 12 Other (Specify below 16 Asing diameter 12 Injection 18 Concrete tile 18 Casing Joints: Glued 18 Casing Joints: Glued 18 Casing Joints: Glued 18 Casing height above land surface 19 Other (specify below) 18 Casing height above land surface 19 Other (specify below) 19 Other (specify) 19 Other (specify) 19 Other (specify below) 19 Other (specify) 19 Oth
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 12 Other (Specify below 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well was a chemical/bacteriological sample submitted to Department? Yes
Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes
Was a chemical/bacteriological sample submitted to Department? Yes
TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded. 2 PVC 4 ABS 7 Fiberglass Threaded. 3 Stain to 9 ft., Dia in. to ft., Dia in. to 5 Casing height above land surface 6 in. to 7 in., weight 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 5 CREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 5 CREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 5 CREEN-PERFORATED INTERVALS: From ft. to ft., From ft., From ft. to ft., From ft.,
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded. Blank casing diameter 5 in. to 9 ft. Dia in. to ft., Dia in. to Casing height above land surface in., weight Ibs./ft. Wall thickness or gauge No. S DR-2 Corvered SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) 5 CREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 5 Gauzed wrapped 9 Drilled holes 5 CREEN-PERFORATED INTERVALS: From ft. to ft., From ft., To ft., From ft
Blank casing diameter 5 in. to 9 ft., Dia in. to 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 9 Drilled holes 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft.,
Blank casing diameter 5 in to 9 ft. Dia in to ft. Dia in to Casing height above land surface in, weight libs./ft. Wall thickness or gauge No. SDR-26 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Baw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft.,
Casing height above land surface. In., weight Ibs./ft. Wall thickness or gauge No. S. C.
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From. 9 ft. to 10 ft., From ft.
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hot 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From. 9 ft. to /O.0 ft., From ft. to From. ft. to GRAVEL PACK INTERVALS: From. NONE ft. to From ft. to From ft. to From ft. to From ft. to GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water we 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
SCREEN-PERFORATED INTERVALS: From
From ft. to ft., From ft., From ft. to f
GRAVEL PACK INTERVALS: From. From tt. to ft., From tt. to From tt. to ft., From tt. to GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From ft. to ft., From ft. to ft., From ft. to What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
From ft. to ft., From ft. to GROUT MATERIAL: Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From O. ft. to 7 ft., From ft. to ft., From ft. to ft., From ft. to What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water we 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From
Grout Intervals: From
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
Direction from well? Narth IN Pasture How many feet? 300
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS
0 2 70p Soil 72 80 Shale DK Gray
2 4 Clay Yel 80 92 Lime, Almost White
2 4 Clay Yel 80 92 Line Almost While 4 9 Line TAN 92 96 Shale Gray 96 15 Shale Gray 96 97 Line Live
9 15 Shale Gray 96 97 LIME Lite
9 15 Shale Gray 96 97 LIME Lite 15 16 LIME Gray 97 100 Shale Gray
16 22 Shale Olive Gray
22 24 Lime Lite
24 31 Red Rock,
31 36 Line, Lite TAN
53 56 Red Rock
53 56 Red Rock 56 63 Shale Gray
53 56 Red Rock 56 63 Shale Gray 63 66 Ling Gray
53 56 Red Rock 56 63 Shale Gray 63 66 Line Gray 60 68 Shale Gray
53 56 Red Rock 56 63 Shale Gray 63 66 Line Gray 60 68 Shale Gray 68 72 Gas Sand (NOGAS)
53 56 Red Rock 56 63 Shale Gray 63 66 Line Gray 68 68 Shale Gray 68 72 Gas Sand (No GAS) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction a
53 56 Red Rock 56 63 Shale Gray 63 66 Line Gray 68 72 Gas Sava (No GAS) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction a completed on (mo/day/year) 54/13.96 and this record is true to the best of my knowledge and belief.
53 56 Red Rock 56 63 Shale Gray 63 66 Line Gray 68 72 Gas Sand (NOGAS) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction a
53 56 Red Rock 56 63 Shale Gray 68 68 Shale Gray CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction a and this record is true to the best of my knowledge and belief.