

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Brown	SW 1/4 SE 1/4 SE 1/4	26	T 1 S S	R 15 E E/W

Distance and direction from nearest town or city street address of well if located within city?

West side of Walnut at Elliot, Morrill

2 WATER WELL OWNER: KDHE-BER	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: Forbes Field, Building 740	Application Number:
City, State, ZIP Code: Topeka, Kansas 66620	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 53 ft. ELEVATION: 1137.5 ft.			
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. 1137.5 ft.			
	WELL'S STATIC WATER LEVEL 40.4 ft. below land surface measured on mo/day/yr 2/28/95			
	Pump test data: Well water was ft. after hours pumping gpm			
	Est. Yield . NA gpm: Well water was ft. after hours pumping gpm			
	Bore Hole Diameter 8 in. to 60 ft., and in. to ft.			
WELL WATER TO BE USED AS:				
1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	11 Injection well
2 Irrigation	4 Industrial	7 Lawn and garden only	10 Monitoring well	12 Other (Specify below)
Was a chemical/bacteriological sample submitted to Department? Yes.....No..... X; If yes, mo/day/yr sample was submitted				
Water Well Disinfected? Yes No X				

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below) Welded
2 PVC	4 ABS	7 Fiberglass	Threaded... X
Blank casing diameter 4 in. to 13 ft., Dia in. to ft., Dia in. to ft.			
Casing height above land surface 3.1 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	7 PVC
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)
			9 ABS
			10 Asbestos-cement
			11 Other (specify)
			12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	11 None (open hole)
		7 Torch cut	9 Drilled holes
			10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 13 ft. to 53 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 12 ft. to 60 ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 10 ft., From 10 ft. to 12 ft., From ft. to ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	Grainstorage.....
Direction from well? W		How many feet? 500		

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Clay, Dark Brown			MW2S
2	7	Clay, Medium Brown			GeoCore # 114 Flushmount
7	11	Clay, Medium Red Brown			KDHE # Tag # 117144
11	14	Clay, Medium Brown			
14	14.2	Limestone, Tan to Yellow Brown			
14.2	22	Shale, Yellow Brown			
22	25	Limestone, Light Gray to Cream			
25	29.5	Shale, Medium to Dark Red Brown			
29.5	31.5	Limestone, Light Gray			
31.5	35.5	Shale, Red Brown to Brown			
35.5	36	Limestone, Gray Brown			
36	46	Shale, Green Brown to Yellow Brown			
46	54	Shale, Gray Green to Pale Green			
54	60	Shale, Gray Green to Pale Green			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2/28/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 3/6/95 under the business name of GeoCore Services, Inc. by (signature) Dale Roll
