WATER WEL	L RECORD	Form WWC-5	Division of Water Resources App. No.
	OF WATER WELL:	Fraction SE ¼ SW ¼ SW ¼ NW	Section Number Township No. Range Number 1/4 35 T 1 S R 17 \(\subseteq E \subseteq W\)
			Global Positioning System (GPS) information:
from nearest town or intersection: If at owner's address, check here . Latitude:39.92.1333			
			Longitude: -95.487800 (in decimal degrees)
1/2 mile South and 1/8 mile East of 290th and Mulberry Rd.			Elevation: 1112'
		<u>Datum</u> : ☐ WGS 84, ☑ NAD 83, ☐ NAD 27	
2 WATER WE	1.0114.4	Farms Inc.	Collection Method:
RR#, Street Address, Box #: 1606 280th St.			GPS unit (Make/Model: Garmin 12xl)
City, State, ZI	P Code : Hiawath	na, KS 66434	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey
			Est. Accuracy:
3 LOCATE WEI			•
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 110			
SECTION BOX: Depth(s) Groundwater Encountered (1).99			ft. (3)
WELL SSITTIC WITCH ED VERSION THE SUITAGE MEMBERS OF MORALLY JULY AND			
Pump test data: Well water was			
EST. YIELD. 100gpm. Well water was			
W			
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well			
Domestic Feedlot Oil field water supply Dewatering Other (Specify below)			
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes V No			
S If yes, mo/day/yr sample was submitted			
1 mile Water well disinfected? ☑ Yes ☐ No			
5 TYPE OF CASING USED: Steel PVC Other			
CASING JOINTS: V Glued Clamped Welded Threaded			
Casing diameter 8 in. to .110 ft., Diameter in. to			
Casing height above land surface. 24 in., Weight 5.39 lbs./ft., Wall thickness or gauge No0.322			
TYPE OF SCRE	EN OR PERFORATION	MATERIAL:	
☐ Steel ☐ Stainless Steel			
Brass Galvanized Steel None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:			
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)			
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)			
SCREEN-PERFORATED INTERVALS: From			
From			
GRAVEL PACK INTERVALS: From			
From ft. to ft., From ft. to ft.			
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☐ Bentonite ☐ Other			
Grout Intervals:			ft. to ft., From ft. toft.
What is the nearest source of possible contamination:			
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)			
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedward Fertilizer storage Oil well/gas well None			
The water tight sower times to be page by the times are the same to be a second to the same times are the same times to the same times are the sam			
			TO LITHO. LOG (cont.) or PLUGGING INTERVALS
FROM TO	LITHOLOG	GIC LOG FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS
0 4	no sample		
4 68	clay silty brown		
68 90	sand & gravel M-C		
90 111	sand & gravel w/cobbl	es	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged			
under my jurisdiction and was completed on (mo/day/year) .09/29/2009 and this record is true to the obstacled, or plagged			
Kansas Water Well Contractor's License No7.79 This Water Well Record was completed on (pro/day/year) 19/19/2009			
under the business name of Drill-Well, LLC by (signature)			
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies			
(white blue pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Safet 420, Topeka, Kansas 66612-1367.			
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at			
http://www.kdheks.gov/waterwell/index.html.			
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy			