Babcock 1 West

WATER WE	ELL RECORD	Form WV	VC-5	Division of Wate	er Resources App. N	o. L
1 LOCATION OF WATER WELL: County: Brown		Fraction NW ¼ NW ¼ NW	¼ NW ¼	Section Number 10		Range Number
	Address of Well Location;		Global Positioning			
from neares	t town or intersection: If at o	owner's address, check	Latitude: .39.986316 (in decimal degrees)			
140' East of 330th & Mallard Rd. South side of 330th Street.				Longitude: -95.50820 (in decimal degrees)		
				Elevation: 1008		
2 WATER WELL OWNER: Kenneth Babcock				Datum: WGS 8	4, 🗹 NAD 83, 🗀	NAD 27
Tromour Baboook				Collection Method:		
C' C' CID C 1			GPS unit (Make/Model: Garmin 12xl			
City, State, ZIP Code : Hiawath		ia, KS 66434		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m,		
3 LOCATE WELL						
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL .84						
SECTION B	OX: Depth(s) Groundwater Encountered (1).45 ft (2) ft (3) 80 ft					
N	WELL'S STATIC WATER LEVEL44.8ft. below land surface measured on mo/day/yr, 04/19/2010					
Pump test data: Well water was \$1.2ft. after 1.5 hours pumping 290						
EST. YIELD. 350gpm. Well water wasf					hours pum	ning onm
w	E Bore Hole Diam	eter 1.4in. to .84	4fi	., andin.	to	.ft.
WELL WATER TO BE USED AS: Public water supply Geothermal Direction well						njection well
Domestic						
Industrial □ Domestic-lawn & garden □ Monitoring well						
<u> </u>		bacteriological sample s			Yes 🗹 No	
S If yes, mo/day/yr sample was submitted						
1 mile Water well disinfected? ☑ Yes □ No						
5 TYPE OF CASING USED: Steel PVC Other						
CASING JOINTS: M Glued Clamped Welded Threaded						
Casing diameter 8						
Casing height above land surface. 24 in., Weight 7.07lbs./ft., Wall thickness or gauge No0.41"						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
☐ Steel ☐ Stainless Steel						
Brass Galvanized Steel None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
☐ Continuous slot						
SCREEN-PERFORATED INTERVALS: From						
From						
GRAVEL PACK INTERVALS: From						
From						
6 GROUT MATERIAL: Neat cement Cement grout V Bentonite Other						
Grout Intervals: From .5						
What is the nearest source of possible contamination:						
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below)						
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well						
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well Road						
				rom well40'		
FROM TO	LITHOLOG	IC LOG	FROM	TO LITHO. LO	JG (cont.) or PLU	IGGING INTERVALS
0 4	no sample					
4 31	clay silty brown			-		
31 45	clay sandy brown					
45 70	sand F-M brown				***************************************	
70 75	sand M-C brown					
75 84	sand & gravel				1.00	
84	limestone					
			<u> </u>	<u> </u>		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged						
under my jurisdiction and was completed on (mo/day/year) .03/05/2010 and this record is true to the best of my knowledge and belief.						
Kansas Water Well Contractor's License No779 This Water Well Record was completed on (mo/day/year) .05/03/2010						
under the business name of Drill-Well, LLC						
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.						
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at						
http://www.kdheks.gov/waterwell/index.html.						
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy						