

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

SE NW

1. Location of well: County DONIPHAN Fraction SE 1/4 NE 1/4 SW 1/4 Section number 9 Township number T 1 S Range number R 19 E

2. Distance and direction from nearest town or city: 3 1/2 mi SE 1/4 NE of White Cloud, Ks
Street address of well location if in city: _____
3. Owner of well: City of White Cloud
R.R. or street: White Cloud
City, state, zip code: KANSAS 66094

4. Locate with "X" in section below: Sketch map:
N
W E
S
1 Mile
SEE ATTACHED SHEET
Larry Wagoner
595-3248

6. Bore hole dia. 9 3/4 in. Completion date Oct 10, 80
Well depth 715 ft.

7. Cable tool Rotary Driven Dug
 Hollow rod Jetted Bored Reverse rotary

8. Use: Domestic Public supply Industry
 Irrigation Air conditioning Stock
 Lawn Oil field water Other

9. Casing: Material _____ Height: Above or below
Threaded _____ Welded _____ Surface 12 in.
RMP _____ PVC Weight _____ lbs./ft.
Dia. 6 1/2 in. to 715 ft. depth Wall Thickness: inches or
Dia. _____ in. to _____ ft. depth gage No. 200 PSE

5. Type and color of material	From	To
SAND Br F-UF	0	12
Silt & clay Br	12	15.5
SAND GRAY F-UF	15.5	19
SAND GRAY med-F	19	32
SAND & GRAVEL C-F	32	35.5
SAND & GRAY C-F SOME GRAVEL	35.5	40
SAND GRAY C-F SOME GRAVEL Lignite	40	47
SAND & GRAVEL GRAY	47	55
SAND & GRAVEL GRAY SOME CLAY	55	62
SAND GRAY C-F SOME GRAVEL	62	66
GRAVEL & SAND GRAY & Boulders	66	72.2
LS med GRAY	72.2	73
TD		

10. Screen: Manufacturer's name UOP
Johanson
Type wirewound Dia. 6"
Slot/gauze 060 Length 5'
Set between 62.5 ft. and 71.5 ft.
Gravel pack? NO Size range of material _____

11. Static water level: _____ mo./day/yr.
13.42 ft. below land surface Date Nov 26 80

12. Pumping level below land surfaces:
32.10 ft. after 2.5 hrs. pumping 75 g.p.m.
_____ ft. after _____ hrs. pumping _____ g.p.m.
Estimated maximum yield 3.81 gpm/ft g.p.m.

13. Water sample submitted: _____ mo./day/yr.
 Yes No Date Nov 27 1980

14. Well head completion:
 Pitless adapter 12 inches above grade

15. Well grouted? yes
With: Neat cement Bentonite Concrete
Depth: From 4 ft. to 215 ft.

16. Nearest source of possible contamination: NONE
ft. _____ Direction _____ Type _____
Well disinfected upon completion? Yes No

17. Pump: _____ Not installed
Manufacturer's name wehr
Model number 3585107B HP 1 Volts 230
Length of drop pipe 45 ft. capacity 35 g.p.m.
Type:
 Submersible Turbine
 Jet Reciprocating
 Centrifugal Other

18. Elevation: 849 855 LS
Topography:
 Hill
 Slope
 Upland
 Valley

19. Remarks:
GRout was set in 10" casing BORE
Diameter 11"

20. Water well contractor's certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Rieschick Drilling License No. 308
Business name _____
Address 1401 McLean St.
Signed Ray Rieschick Date Dec 4, 80
Authorized representative

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5

Elevation changed from 907

T 1 S R 19 E