

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: WASHINGTON	NW 1/4 NW 1/4 NE 1/4	8	T 1 S	R 5E EW

Distance and direction from nearest town or city street address of well if located within city?
 6 1/2 north and 1/2 west of Hanover

2 WATER WELL OWNER: Washington Co. RWD #1 WELL #11
 RR#, St. Address, Box # : Rt. 1 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Hanover, KS 66945 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL... 123.11 ft. ELEVATION:

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL .. 64 ft. below land surface measured on mo/day/yr ... 8-28-95

Pump test data: Well water was 83' - 10" ft. after 2 hours pumping ... 150 gpm

Est. Yield .. 150 .. gpm: Well water was 85' - 7" ft. after 8 hours pumping ... 150 gpm

Bore Hole Diameter..... in. to ft., and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes... No.....; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued	Clamped
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded .. <input checked="" type="checkbox"/>	Threaded
Blank casing diameter 8 in. to 93.11 ft., Dia		7 Fiberglass		8 Saw cut	
Casing height above land surface..... 24 in., weight 28.55 lbs./ft. Wall thickness or gauge No. 322		10 Asbestos-cement		11 None (open hole)	

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify) .. .030 slott	

SCREEN-PERFORATED INTERVALS: From 93.11 ft. to 123.11 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 74 ft. to 123.11 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other .50-50 Bentonite & Sand

Grout Intervals: From 5 ft. to 25 ft., From ft. to ft., From 25 ft. to 74 ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? nothing within 1/2 mile How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top Soil			
2	35	Brown Clay			
35	49	Tan Clay-iron stone			
49	55	Tan Shale, weathered			
55	59	Grey Shale			
59	61	Tan Shale - iron stone			
61	65	Grey Shale			
65	68	Brown Sandstone			
68	70	Grey Shale			
70	79	Brown Sandstone-loose			
79	80	Rionstone			
80	85	Brown Sandstone			
85	119	Brown Sandstone-loose			
119	123.11	Grey Limestone			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-30-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. ... 182 This Water Well Record was completed on (mo/day/yr) 11-28-95 under the business name of STRADER DRILLING CO., INC. by (signature) Dale Strader