

WATER WELL RECORD Form WWC-5

Original Record Correction Change in Well Use


Division of Water Resources App. No.

Well ID

1 LOCATION OF WATER WELL: County: WASHINGTON Fraction NE 1/4 NW 1/4 NW 1/4 Section Number 16 Township Number T 1 S Range Number R 5 E W

2 WELL OWNER: Last Name: MEYER First: RICHARD Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): EAST OF HANOVER ON HWY 148 4 1/2 NORTH, 1 WEST AND 1 NORTH

3 LOCATE WELL WITH "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 74 ft. Depth(s) Groundwater Encountered: 1) 74 ft. 2) 49 ft. WELL'S STATIC WATER LEVEL: 49 ft. below land surface, measured on (mo-day-yr) 10/11/2014

5 Latitude: 39° 58.404' N (decimal degrees) Longitude: 96° 52.751' W (decimal degrees) Datum: WGS 84 NAD 83 NAD 27 Source for Latitude/Longitude: GPS (unit make/model: WAAS enabled? Yes No) Land Survey Topographic Map Online Mapper:

6 Elevation: Ground Level TOC Source: Land Survey GPS Topographic Map Other

7 WELL WATER TO BE USED AS: 1. Domestic: [X] Household [] Lawn & Garden [X] Livestock 2. Irrigation 3. Feedlot 4. Industrial 5. Public Water Supply: well ID 6. Dewatering: how many wells? 7. Aquifer Recharge: well ID 8. Monitoring: well ID 9. Environmental Remediation: well ID 10. Oil Field Water Supply: lease 11. Test Hole: well ID 12. Geothermal: how many bores? 13. Other (specify):

Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted: Water well disinfected? Yes No

8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter: 5 in. to 44 ft., Diameter: in. to ft., Diameter: in. to ft. Casing height above land surface: 18 in. Weight: 2.8 lbs./ft. Wall thickness or gauge No.: 265

TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel Fiberglass PVC Other (Specify) Brass Galvanized Steel Concrete tile None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole)

SCREEN-PERFORATED INTERVALS: From 44 ft. to 74 ft., From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 74 ft., From ft. to ft., From ft. to ft.

9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From 4 ft. to 20 ft., From ft. to ft., From ft. to ft.

Nearest source of possible contamination: Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Other (Specify) NONE PRESENT

Table with 6 columns: 10 FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Rows: 0-2 TOPSOIL, 2-42 TAN CLAY, 42-55 SANDSTONE LAYERS, 55-81 RED SHALE. Includes a Notes section.

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) 10/11/2014 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 518 This Water Well Record was completed on (mo-day-year) 10/11/2014 under the business name of BLUE VALLEY DRILLING INC. Dan Arch