

# WATER WELL RECORD

### DRILLERS LOG OF WELL

| FROM (FT.) | TO (FT.) | KIND OF MATERIAL, COLOR, ETC. (NOTE WATER ZONES, AMOUNT, QUALITY) |
|------------|----------|---|
| 0          | 4        | Soil  |
| 4          | 32       | LS, white & yellow  |
| 32         | 45       | Shale, gray   |
| 45         | 125      | Sand, white (*)   |
| 125        | 135      | Shale, gray   |
| 135        | 150      | Sand  |
|            |          |   |
|            |          |   |
|            |          |   |
|            |          |   |
|            |          |   |
|            |          |   |
|            |          |   |
|            |          |   |
|            |          |   |
|            |          |   |
|            |          |   |
|            |          |   |
|            |          |   |
|            |          |   |
|            |          |   |
|            |          |   |
|            |          |   |

LANE BARNETT SPRINGS SHALE  
 REINFORC 2"


Well Owner Hoyt Brothers  
 Address \_\_\_\_\_  
 Drilling Contractor H. R. Swank  
Princeton, Kans  
 Date Drilled April 1954  
 Method of Drilling Cable Tools  
 Casing: Set 10 ft of 6 1/4 Steel used  
(New, Used, Steel, Galv., Gage or Weight)  
 Casing Schedule: \_\_\_\_\_  
(Amount, Size, Setting)  
 Screen Data (if any): \_\_\_\_\_

### ON COMPLETED WELL

Measured depth to water (Static Level) is \_\_\_\_\_ ft.  
 below \_\_\_\_\_  
(Land Surface, Top of Casing, Etc.)  
 TESTED YIELD: \_\_\_\_\_ gallons per \_\_\_\_\_  
(Mts., Hour)  
 as determined by \_\_\_\_\_  
(Bailing, Test Pumping, Etc.)  
 DRAWDOWN: \_\_\_\_\_ ft. after \_\_\_\_\_ hrs.  
 pumping at \_\_\_\_\_ gal. per minute.  
 REMARKS: yield fair  
Drilled 6 1/4 in hole  
SW corner of Garnett

#### LOCATION OF WELL

[Show location in Section Plat] Elev. \_\_\_\_\_  
 NW 1/4 NE 1/4 Sec. 36  
 T. 20 S., R. 19 E. W.  
 County Anderson



"To preserve water well information and to promote the conservation, protection, and development of ground-water resources."