


1 LOCATION OF WATER WELL: County: Marion Fraction: SW 1/4 NW 1/4 NW 1/4 Section Number: 3 Township Number: T 20 S Range Number: R 2 E

Distance and direction from nearest town or city street address of well if located within city? 701 S. Main St. Hillsboro, KS

2 WATER WELL OWNER: Salems Hospital RR#, St. Address, Box #: 701 S. Main City, State, ZIP Code: Hillsboro, KS Board of Agriculture, Division of Water Resources Application Number: Murp

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  DEPTH OF COMPLETED WELL: 25 ft. ELEVATION: 1413.67 ft. Depth(s) Groundwater Encountered 1. 1405.32 ft. 2.            ft. 3.            ft. WELL'S STATIC WATER LEVEL 8.35 ft. below land surface measured on mo/day/yr 5/17/99 Pump test data: Well water was            ft. after            hours pumping            gpm Est. Yield            gpm: Well water was            ft. after            hours pumping            gpm Bore Hole Diameter 8 in. to 25 ft., and            in. to            ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes            No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes            No           

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 4 ABS 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued            Clamped            6 Asbestos-Cement 9 Other (specify below) Welded            7 Fiberglass Threaded X Blank casing diameter 2 in. to 5 ft., Dia            in. to            ft., Dia            in. to            ft. Casing height above land surface Flush in., weight            lbs./ft. Wall thickness or gauge No.            TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)            2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 0 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)            7 Torch cut SCREEN-PERFORATED INTERVALS: From 25 ft. to 5 ft., From            ft. to            ft. GRAVEL PACK INTERVALS: From 25 ft. to X 3 ft., From            ft. to            ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other            Grout Intervals: From X 3 ft. to            ft., From            ft. to            ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below)            Direction from well? Southwest How many feet? 40

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>25</u>	<u>Brown + gray silty clay</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-17-99 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 634 This Water Well Record was completed on (mo/day/yr) 5-25-99 under the business name of Smiley Env. Testy LLC by (signature) Murp

OFFICE USE ONLY  
T  
R  
EW  
SEC.  
1/4  
1/4