


1 LOCATION OF WATER WELL: Fraction SW 1/4 NW 1/4 NW 1/4 Section Number 3 Township Number T 20 S Range Number R 2 EW  
 County: Madison  
 Distance and direction from nearest town or city street address of well if located within city? 701 S. Main St., Hillsboro, KS

2 WATER WELL OWNER: Dobson, Harold E  
 RR#, St. Address, Box #: 701 S. Main St. Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: Hillsboro, KS Application Number: MU7

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  DEPTH OF COMPLETED WELL: 25 ft. ELEVATION: 1411.91  
 Depth(s) Groundwater Encountered: 1. 1402.06 ft. 2. — ft. 3. — ft.  
 WELL'S STATIC WATER LEVEL 9.85 ft. below land surface measured on mo/day/yr 5/19/99  
 Pump test data: Well water was — ft. after — hours pumping — gpm  
 Est. Yield — gpm; Well water was — ft. after — hours pumping — gpm  
 Bore Hole Diameter: 8 in. to 25 ft., and — in. to — ft.  
 WELL WATER TO BE USED AS:  
 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes — No X; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes — No X

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued — Clamped —  
2 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded —  
 Blank casing diameter 2 in. to 5 ft., Dia — in. to — ft., Dia — in. to — ft.  
 Casing height above land surface Fresh in., weight — lbs./ft. Wall thickness or gauge No. —  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify) —  
 SCREEN-PERFORATED INTERVALS: From 25 ft. to 5 ft., From — ft. to — ft.  
 GRAVEL PACK INTERVALS: From 25 ft. to X3 ft., From — ft. to — ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other —  
 Grout Intervals: From X3 ft. to — ft., From — ft. to — ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage  
 Direction from well? northwest How many feet? 90

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>25</u>	<u>Gray + brown silty clay</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-17-99 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 634 This Water Well Record was completed on (mo/day/yr) 5-25-99 under the business name of Stanley Eng. Testing LLC by (signature) [Signature]

OFFICE USE ONLY  
T  
R  
EW  
SEC.  
1/4  
1/4  
1/4