WATER WELL RECORD Form WWC-5 Division of Water Resources App. No.
1 LOCATION OF WATER WELL: Fraction Section Number Township No. Range Number County: Linn NW 1/4 SW 1/4 NE 1/4 1/4 26 T 20 S R 23 ZIE DW
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information:
from nearest town or intersection: If at owner's address, check here . Latitude: .38.17'.97" (in decimal degrees) Longitude: 94.49'.38.41" (in decimal degrees)
Elevation:
2 WATER WELL OWNER: Jack Deveo Collection Method:
RR#, Street Address, Box #: 925 W. Lakeside Dr.
City, State, ZIP Code : LaCvone, Kansas 66040 Digital Map/Photo, Topographic Map, Land Survey Est. Accuracy: 3 m, 3-5 m, 5-15 m
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 350 ft.
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 350 ft. SECTION BOX: Depth(s) Groundwater Encountered (1).310 ft. (2) ft. (3) ft.
SECTION BOX: Depth(s) Groundwater Encountered (1).310 ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL130 ft. below land surface measured on mo/day/yr
Pump test data: Well water wasft. after hours pumping gpm
POT VIELD 5
W NW NE EST. TIELD 3gpm. Well water was
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well
SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No If yes, mo/day/yr sample was submitted
Water well disinfected?
5 TYPE OF CASING USED: Steel PVC Other
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 5
Casing height above land surface 18 in., Weight 220 PSI lbs./ft., Wall thickness or gauge No.
TYPE OF SCREEN OR PERFORATION MATERIAL:
Steel Stainless Steel PVC Other (Specify)
Brass Galvanized Steel None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)
SCREEN-PERFORATED INTERVALS: From 300 ft. to 350 ft., From ft. to ft.
From
From
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other
Grout Intervals: From 0 ft. to 30 ft. From ft. to ft., From ft. to ft.
What is the nearest source of possible contamination:
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well
Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well
Direction from well North Distance from well 50.
FROM TO LITHOLOGIC LOG FROM TO LITHO. LOG (cont.) or PLUGGING INTERVALS
0 6 Clay
6 27 Limestone
27 31 Black Shale
65 Limestone 65 Shale
310 330 Sandy Shale
330 350 Sandstone
OU OU GRIDSIONS
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged
under my jurisdiction and was completed on (mo/day/year) 12/13/109 and this record is true to the best of my knowledge and belief.
Kansas Water Well Contractor's License No
under the business name of LESC TOXALUM WELL DIMING by (signature)
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies
(white blue pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1600 SW Jackson St., Suite 420, Topekal Kansas 66612-1367.
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records.—Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy