

1 LOCATION OF WATER WELL: County: LINN	Fraction ¼ PT NW ¼ NE ¼	Section Number 14	Township Number T 20 S	Range Number R 24E EW
--	-----------------------------------	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?
Two miles east and two miles south of LaCygne.

2 WATER WELL OWNER: **Robert Wolfenberger**
 RR#, St. Address, Box #: **P. O. Box 415**
 City, State, ZIP Code: **La Cygne, KS 66040**
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

	4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 33 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: 20 ft. below land surface measured on mo/day/yr 9/5/92 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 15 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: 8 in. to 80 ft., and in. to ft. WELL WATER TO BE USED AS: <input checked="" type="checkbox"/> 1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well <input type="checkbox"/> 2 Irrigation 4 Industrial 7 Lawn and garden only 9 Dewatering 12 Other (Specify below) 5 Public water supply 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No..... <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No
--	--

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped
<input checked="" type="checkbox"/> 2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
Blank casing diameter: 5 in. to 33 ft., Dia. in. to ft.		7 Fiberglass	Threaded	
Casing height above land surface: 18 in., weight lbs./ft. Wall thickness or gauge No. Sch 40		TYPE OF SCREEN OR PERFORATION MATERIAL:		
1 Steel	3 Stainless steel	5 Fiberglass	<input checked="" type="checkbox"/> 7 PVC	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	<input checked="" type="checkbox"/> 3 Mill slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 33 ft. to 80 ft., From ft. to ft.		GRAVEL PACK INTERVALS: From 33 ft. to 80 ft., From ft. to ft.		

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From **0** ft. to **33** ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? How many feet? **55 ft**

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Soil			
3	36	Clay			
36	40	Sand/Gravel			
40	65	Light Shale			
65	70	Red Bed			
70	80	Shale - TD			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) **9/8/92** and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. **338**. This Water Well Record was completed on (mo/day/yr) **9/16/92** under the business name of **Jayhawk Drilling** by (signature) *Thomas F Moyer*

OFFICE USE ONLY