


1 LOCATION OF WATER WELL: Fraction $\frac{1}{4}$ W $\frac{1}{2}$ SW $\frac{1}{4}$ Section Number 14 Township Number T 20 S Range Number R 3 **EW**
 County: Marion
 Distance and direction from nearest town or city street address of well if located within city?
 3 mi SW of Marion MW-5A

2 WATER WELL OWNER: Marion County Landfill, Inc.
 RR#, St. Address, Box #: P.O. Box 115
 City, State, ZIP Code: Peabody, KS 66836
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 23.5 ft. ELEVATION: 1351.5 ft.
 Depth(s) Groundwater Encountered: 1. 14.0 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL: 13.58 ft. below land surface measured on mo/day/yr 8/15/96
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 6 3/8 in. to TD ft., and in. to ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes **No**

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 7 Fiberglass Welded
 Blank casing diameter 2 in. to ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 20 in., weight lbs./ft. Wall thickness or gauge No. 40
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 4 Milk slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 13 ft. to 23 ft. From ft. to ft.
 GRAVEL PACK INTERVALS: From 20/40 10.8 ft. to 23.5 ft. From ft. to ft.
 From 50/100 8.8 ft. to 10.8 ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 2 ft. to 8.8 ft., From 23.5 ft. to 35.2 ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 Direction from well? West How many feet? 50
 Landfill

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2.5	Soil			
2.5	7.8	Soft, Clayey LS			
7.8	14.0	Claystone			
14.0	15.5	LS, solutional			
15.5	21.7	Mudshale			
21.7	24.8	LS			
24.8	35.2	Clay shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-9-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 568 This Water Well Record was completed on (mo/day/yr) 8-9-96 under the business name of Max's by (signature) David [unclear]

OFFICE USE ONLY
T
R
EW
SEC.
1/4
1/4
1/4