

1 LOCATION OF WATER WELL: Fraction $\frac{1}{4}$ W $\frac{1}{2}$ SW $\frac{1}{4}$ Section Number 14 Township Number T 20 S Range Number R 3 **(EW)**

County: Marion
 Distance and direction from nearest town or city street address of well if located within city?
 3 mi SW of Marion MW-6A

2 WATER WELL OWNER: Marion County Landfill, Inc.
 RR#, St. Address, Box #: P.O. Box 115
 City, State, ZIP Code: Peabody, KS 66836
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 4x4 grid with NW, NE, SW, SE quadrants and an 'X' in the SW quadrant.]
 4 DEPTH OF COMPLETED WELL: 25 ft. ELEVATION: 1358.2
 Depth(s) Groundwater Encountered 1. 14.5 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL 17.45 ft. below land surface measured on mo/day/yr 8/15/96

Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter 6 3/8 in. to TD ft., and in. to ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes **(N)**

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded

Blank casing diameter 2 in. to ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 25 in., weight lbs./ft. Wall thickness or gauge No. 40

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 14.5 ft. to 24.5 ft. From ft. to ft.
 From ft. to ft. From ft. to ft.
 GRAVEL PACK INTERVALS: From 20/40 13 ft. to 25 ft. From ft. to ft.
 From 50/100 11 ft. to 13 ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 2 ft. to 11 ft. From 25 ft. to 50 ft. From ft. to ft.

What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 Landfill
 Direction from well? North How many feet? 150

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.8	Soil			
0.8	4.2	soft, clayey limestone			
4.2	9.9	Claystone			
9.9	21.8	ls, fractured, solutional			
21.8	28.0	Mudshale			
28.0	33.2	ls, fractured			
33.2	50.0	Clayshale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was **(1)** constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-9-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 568 This Water Well Record was completed on (mo/day/yr) 8-9-96 under the business name of MAXS by (signature) David Humphreys