

1	LOCATION OF WATER WELL: County: <u>Marion</u>	Fraction <u>Me 1/4 Me 1/4 NW 1/4</u>	Section Number <u>16</u>	Township Number T <u>20</u> 19 S	Range Number R <u>43</u> 42 <u>EW</u>
---	--	---	-----------------------------	--	---


Distance and direction from nearest town or city street address of well if located within city?
1 1/2 S 3 1/2 E Marion

2 WATER WELL OWNER: Jim Schlehuber

RR#, St. Address, Box # : RR2 Box 65-
City, State, ZIP Code : Marion, KS 66861

Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL 78 ft. ELEVATION:



Depth(s) Groundwater Encountered 1 70 ft. 2 ft. 3 ft.
WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on mo/day/yr 3-13-04
Pump test data: Well water was ft. after hours pumping gpm
Est. Yield 20 gpm: Well water was ft. after hours pumping gpm
WELL WATER TO BE USED AS:
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
Water Well Disinfected? (Yes) No

5 TYPE OF BLANK CASING USED:
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
7 Fiberglass Threaded

Blank casing diameter 5 in. to 58 ft. Dia in. to ft. Dia in. to ft.
Casing height above land surface 12 in., weight 0.1255/60 lbs./ft. Wall thickness or guage No. 2.14

TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement
2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify)
9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 58 ft. to 78 ft., From ft. to ft.
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage
Direction from well? S How many feet? 100 +

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>6</u>	<u>Clay</u>			
<u>6</u>	<u>22</u>	<u>lime</u>			
<u>22</u>	<u>40</u>	<u>Yellow Shale</u>			
<u>40</u>	<u>52</u>	<u>Red Shale</u>			
<u>52</u>	<u>70</u>	<u>Yellow Shale + mixed lime</u>			
<u>70</u>	<u>71</u>	<u>Broken Lime + Water</u>			
<u>71</u>	<u>78</u>	<u>lime</u>			
<u>75</u>	<u>78</u>	<u>Gray Rock Hard</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-13-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 180 This Water Well Record was completed on (mo/day/yr) 3-29-04 under the business name of Backhoe Drilling by (signature) Paul H. Backhoe