CORRECTION TO WATER WELL RECORD (WWC-5)

The following correction(s) was made to the attached WWC-5 log, in order to file the item or to rectify lacking or incorrect information.

Fraction (1/4 1/4) Section-Township-Range changed:
listed as NE, NE, NW, 3/-205-5E
changed to <u>NE</u> , NE, NW, 3/-205-6E
Other changes: Initial statements:
Changed to:
Comments:
verification method: Written description on form, position on plat map Ledar Point, 15, 1:24,000 topo, map initials: ARL date: 2/3/99 submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726

to: Kansas Dept of Health & Environment Bureau of Water Industrial Programs, Bldg 283, Forbes Field, KS 66620

			LL RECORD	Form WWC-5	KSA 828	a-1212			
ounty: Cha	le	Fraction 1/4		W 1/4	ion Number	T 2	umber 7 s	Range Nun	nber EXV
tance and direction		or city street address	s of well if located ないれて	d within city?	•				
LIV 2									
WATER WELL OV	WEH: DICHO	end B. Pe	Ynor			December 6			D
#, St. Address, Bo	×# : 1634	Wi Me, A	L'ENDY D	210			•	ivision of Water	Hesources
, State, ZIP Code		Alta, KS	67	4			n Number:		
OCATE WELL'S L IN "X" IN SECTIO		DEPTH OF COMP Depth(s) Groundwater		45	. ft. ELEVA	ATION: 2	ft. 3.		ft
X		VELL'S STATIC WAT		. ≨ ft. b∈	elow land su	rface measured or	n mo/day/yr	6-10-	- 86
1 '	1 1					after			
NW		st. Yield 3 .0.	gpm: Well water	r was	ft. ε	after	. hours pun	nping	gpm
w		Bore Hole Diameter.	•						nt.
	l ! \^	VELL WATER TO BE		5 Public water		8 Air conditioning	•	njection well	
sw	SE	1 Domestic		6 Oil field wat		9 Dewatering		Other (Specify be	elow)
		2 Irrigation		-	-	10 Observation w	_		
<u> </u>	'	Vas a chemical/bacte	riological sample s	submitted to De	-	•			e was sub
	ş <u> n</u>	nitted			Wa	ater Well Disinfecte		17	
TYPE OF BLANK	CASING USED:	5 V	Vrought iron	8 Concre	te tile	CASING JO	INTS: Glued	. X Clamped	d
1 Steel	3 RMP (SR)	6 A	sbestos-Cement	9 Other (specify belo	w)	Welde	d	
2 PVC	4 ABS		iberglass					ded	
nk casing diameter	·	to	. ft., Dia	n. to, فn. to,		ft., Dia	i i	n. to	ft.
sing height above	and surfacea	to	weight . <equation-block> ./🚓</equation-block>		<i>6.0</i> . lbs.	/ft. Wall thickness	or gauge No	21.19.	
PE OF SCREEN C	R PERFORATION	MATERIAL:		7 PV			bestos-cemer		
1 Steel	3 Stainless s	steel 5 F	iberglass	8 RM	P (SR)	11 Oth	ner (specify)		
2 Brass	4 Galvanized		Concrete tile	9 ABS	s	12 No	ne used (ope	en hole)	
REEN OR PERFO	RATION OPENING	S ARE:	5 Gauze	ed wrapped		8_Saw cut	٠.	11 None (open	hole)
1 Continuous sl	ot 3 Mill	slot		wrapped		9 Drilled holes	7	` '	,
2 Louvered shu		punched	7 Torch			10 Other (specif	(v)		
REEN-PERFORAT	•	From3	ft to	4	ft Fro	om			
MEERY EIN ONN	LD INTERVALO.		ft to			om			
CDAVEL D	CK INTEDVALS	10	ft. to			om			
GRAVEL PA	ACK INTERVALS:	From /		,~~ . ~~			·		
00017		From	ft. to		ft., Fro				ft.
GROUT MATERIA	\sim		ement grout	3 Bento		Other			
			π., From	π.		ft., From .			
	ource of possible of					vestock pens 14 Abandoned water well			well
1 Septic tank	, 4 Lateral					el storage 15 Oil well/Gas well			
2 Sewer lines	5 Cess p		8 Sewage lago	oon		ilizer storage	16 Ot	her (specify belo	ow)
_	ver lines, 6 Seepa	ge pit	9 Feedyard			cticide storage			
rection from well?						any feet? ろろ			
ROM TO	010	LITHOLOGIC LOG		FROM	то		LITHOLOG	C LOG	
0 30	Clay								
	0	a							
0 32	fine	sand							
2 58	Clay								
	^	^							
3 P 4/P	Tinp	Sand							
12 52	Gray	7/21							
	Gray) - U							
									· · ·
	1				L				
CONTRACTOR'S	OR LANDOWNER'	S CERTIFICATION:	This water well w	as (1) constru	cted, (2) red	constructed, or (3)	plugged und	er my jurisdiction	n and wa
empleted on (mo/day	,	18-86				ord is true to the b			
ater Well Contracto		180	This Water W			on (mo /day/y r)		- 850	
	ame of B ac	KhVS		lai		ature)		rethus	
		oint pen, PLEASE PR					e or circle the	correct answers	s. Send to
ee copies to Kansa	s Department of Hea	alth and Environment,							
VNER and retain of	ne for your records	· ·				· .			