


1 LOCATION OF WATER WELL: Fraction SE 1/4 SE 1/4 SE 1/4 Section Number 3 Township Number T 20 S Range Number R 8 (EW)
 County: Chase

Distance and direction from nearest town or city street address of well if located within city?
2 mile East & 2 mile South of Cottonwood Falls

2 WATER WELL OWNER: Dough Cahone
 RR#, St. Address, Box #: RR1 Box 56 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Cottonwood Falls 66845 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 14 ft. 2. 14 ft. 3. 60 ft.
 WELL'S STATIC WATER LEVEL: 14 ft. below land surface measured on mo/day/yr Nov 19 95
 Pump test data: Well water was 18 ft. after 60 hours pumping 18 gpm
 Est. Yield 18 gpm Well water was 25 ft. after 60 hours pumping 6 1/2 gpm
 Bore Hole Diameter: 8 5/8 in. to 25 ft., and 6 1/2 in. to 60 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 5 Public water supply 6 Oil field water supply 7 Lawn and garden only 8 Air conditioning 9 Dewatering 10 Monitoring well 11 Injection well 12 Other (Specify below)
 Was a chemical/bacteriological sample submitted to Department? Yes No No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below)
 Blank casing diameter 5 in. to 17 ft., Dia. 17 in. to 60 ft., Dia. 60 in. to 60 ft.
 Casing height above land surface 18 in., weight 17 lbs./ft. Wall thickness or gauge No. SDR-26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 RMP (SR) 8 Saw cut 9 Asbestos-cement 10 Other (specify)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify)
 SCREEN-PERFORATED INTERVALS:
 From 17 ft. to 60 ft. From 17 ft. to 60 ft. From 17 ft. to 60 ft.
 GRAVEL PACK INTERVALS:
 From 14 ft. to 60 ft. From 14 ft. to 60 ft. From 14 ft. to 60 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 14 ft. From 14 ft. to 60 ft. From 60 ft. to 60 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)
 Direction from well? South How many feet? 70
Road Ditch

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Top Soil			
3	10	Clay, Brn			
10	21	clay & Gravel			
21	25	LIME-White Soft			
25	33	Shale Gray			
33	36	LIME Lite			
36	38	Shale Gray			
38	40	LIME Gray			
40	49	Shale Blue Green			
49	54	LIME Gray			
54	55	Shale DK Gray			
55	60	LIME White			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) Nov 19 95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 218 This Water Well Record was completed on (mo/day/yr) Nov 27 95 under the business name of ZINN Water Well Dring by (signature) Dough A. Zinn

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T R EW SEC